


PACKAGE: INDIVIDUAL PE BAG.

300g Weight



SEC:A-A

CONDUCTOR: [26AWG (0.12X12) BARE COPPER]X4C  
 INSULATION: (PP6331 ID: 0.95-1.0)X4C  
 JACKET: PVC NOUL 80P (Flexible material)  
 BLACK  
 RED  
 GREEN  
 YELLOW

NOTE FOR PLUG:  
 MATERIAL: HOUSING-POLYCARBONATE, CLEAR.  
 TERMINAL-0.36[.014] THICK PHOSPHOR BRONZE.  
 THICK GOLD IN LOCALIZED GOLD PLATE.  
 AREA, GOLD FLASH OVER THE REMAINDER.  
 OVER 2.54um[.000100] THICK NICKEL  
 UNDERPLATE.

TERMINATION:

P1	P2	COLOR
1	1	BLACK
2	2	RED
3	3	GREEN
4	4	YELLOW

PART NO	DRAWING NO	BUYER COLOR	VENDOR COLOR	RETRACTED LENGTH ("L3")	CUSTOMER Accepted ("L2")	CUT LENGTH "L1"
522-26-4400-WH-0005F	A	White	W-103 LIGHT	330 ± 30	5.0FT-5.75FT	2300-2400
522-26-4400-WH-0007F	B	White	W-103 LIGHT	470 ± 30	7.0FT-8.05FT	3000-3200
522-26-4400-WH-0010F	C	White	W-103 LIGHT	630 ± 50	10.0FT-11.5FT	4300-4500
522-26-4400-WH-0012F	D	White	W-103 LIGHT	800 ± 50	12.0FT-13.8FT	5200-5400
522-26-4400-WH-0014F	E	White	W-103 LIGHT	850 ± 50	14.0FT-16.1FT	5800-6000
522-26-4400-WH-0025F	F	White	W-103 LIGHT	1900 ± 50	25.0FT-28.75FT	10800-11000

REVISE	VERSION	BASIS	CONTENTS
12-02-20	A/0	T0210A	NEW DRAWING

CnC Tech, LLC	
Industrial Cable and Connector Technology	
IDRAWING NO: 671-327	CUSTOMER: L-671
ITEM NO: 4C COILD CORD P+P PLUG	UNIT: mm
DATE: 2012-02-20	ISSUE (A/0)
DRAWN:                   QE:                   QA:	
SALES DEPT:                   SALES MANAGER:	