

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		OPERATING TEMPERATURE RANGE		STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C <sup>(3)</sup>													
△ RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C <sup>(1)(2)</sup>		OPERATING HUMIDITY RANGE	RH 85 % MAX <sup>(2)(4)</sup>													
	VOLTAGE	60 V AC <sup>(5)</sup>		STORAGE HUMIDITY RANGE	RH 70 % MAX <sup>(3)(4)</sup>													
	CURRENT	0.5 A <sup>(6)</sup>		AWG 36, 40 THIN COAXIAL CABLE														
<b>SPECIFICATIONS</b>																		
ITEM	TEST METHOD			REQUIREMENTS		QT AT												
GENERAL EXAMINATION MARKING	VISUALLY AND BY MEASURING INSTRUMENT. CONFIRMED VISUALLY.		ACCORDING TO DRAWING.		x	x												
CONSTRUCTION																		
MARKING																		
<p>△</p> <p>2</p> <p>DESCRIPTION OF REVISIONS</p> <p>DIS-F-004353</p> <p>DESIGNED</p> <p>KN. SHIBUYA</p> <p>CHECKED</p> <p>HT. YAMAGUCHI</p> <p>DATE</p> <p>09.12.15</p> <p>REMARKS</p> <p>(1) INCLUDE TEMPERATURE RISE CAUSED BY CURRENT-CARRYING.</p> <p>(2) OPERATING TEMPERATURE SHOULD BE .55 TO 40°C WHEN HUMIDITY EXCEEDS 80% RH.</p> <p>(3) THE SPECIFICATION IS APPLIED TO THE PRE-ASSEMBLED COMPONENT AND THE CABLE ASSEMBLED PRODUCT BOTH IN DELIVERY AND STORAGE, BEFORE ASSEMBLED TO PCB.</p> <p>(4) THERE MUST NOT BE DEW/FALL.</p> <p>(5) IT IS THE MAXIMUM VALUE OF CONNECTOR. CONFIRM THE SPECIFICATION OF THE CABLE.</p> <p>Unless otherwise specified, refer to JIS-C-5402.</p> <p>Note QT:Qualification Test AT:Assurance Test X:Applicable Test</p> <p>DRAWING NO. ELC4-157684-00</p>																		
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE														
2	DIS-F-004353	KN. SHIBUYA	HT. YAMAGUCHI	09.12.15														
<table border="1"> <tr> <td>APPROVED</td> <td>HS. OKAWA</td> <td>08.04.18</td> </tr> <tr> <td>CHECKED</td> <td>HT. YAMAGUCHI</td> <td>08.04.18</td> </tr> <tr> <td>DESIGNED</td> <td>KN. SHIBUYA</td> <td>08.04.17</td> </tr> <tr> <td>DRAWN</td> <td>KN. SHIBUYA</td> <td>08.04.17</td> </tr> </table>							APPROVED	HS. OKAWA	08.04.18	CHECKED	HT. YAMAGUCHI	08.04.18	DESIGNED	KN. SHIBUYA	08.04.17	DRAWN	KN. SHIBUYA	08.04.17
APPROVED	HS. OKAWA	08.04.18																
CHECKED	HT. YAMAGUCHI	08.04.18																
DESIGNED	KN. SHIBUYA	08.04.17																
DRAWN	KN. SHIBUYA	08.04.17																
<p><b>HRS</b></p> <p>SPECIFICATION SHEET</p> <p>HIROSE ELECTRIC CO., LTD.</p> <p>PART NO.</p> <p>CODE NO.</p> <p>CL575-3312-3-00</p> <p>FX16-31P-GND</p> <p>ELC4-157684-00</p> <p>△</p> <p>1/1</p>																		