

1

2

3

4

5

6

7

A

A

B

B

C

C

D

D

E

E

F

F

G

G

H

H

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)

Dimensions:
 $2,54 \pm 0,10$
 $2,54 \times \text{No.of Positions} - 2,54 \pm 0,20$
 $2,54 \times \text{No.of Positions} + 5,32 \pm 0,25$
 $2,54 \times \text{No.of Positions} + 7,62 \pm 0,30$
 $2,54 \pm 0,10$
 $6,50 \pm 0,15$
 $8,80 \pm 0,15$

Dimensions:
 $2,54$
 $1,02$
 $4,50$
 $10,50$

NOTES:

MATERIAL

⑨ 1. Insulator Material: PA9T+30%GF(UL94V-0), Black
 2. Contact Material : Brass
 3. Contact Plating : Gold flash

ELECTRICAL

1. Current Rating : 3.0AMP
 2. Withstand Voltage : 1000V AC/minute
 3. Contact Resistance : 20mΩ max
 4. Insulation Resistance: 1000MΩ min

ENVIRONMENTAL

1. Operation Temperature: -40°C to +105°C
 2. Packing: Tube+Cap

⑤ 3. Soldering temperature: +260°C(10s)

Order Information

⑩ Contacts xx: 06,08,10,12,14,16,18,20,24
 26,30,34,40,50,60,64

Dimensions:
 $10,00$ CAP ⑥
 $5,90$
 $2,54 \pm 0,10$
 $SQ 0,64$
 $9,00 \pm 0,15$

Dimensions:
 $9,00$
 $10,50$
 $1,00 \pm 0,25$
 $9,50 \pm 0,25$
 $0,15$

RoHS compliant

⑦
File No.: E198287

Scale	Free	⑩	Add 40pin	30.11.2018	Xavier		Date	Name	Customer-No.
TOLERANCE									
X.X	±0.40	⑨	Correct the material to PA9T	22.03.2016	Winnie	Drawn	25.01.2006	Alex	
X.XX	±0.25	⑧	Update the correct part number	11.02.2014	Winnie	Approved	22.03.2016	Winnie	ASSMANN WSW-No.
X.XXX	±0.15	⑦	Add UL-File No	12.12.2013	Amy				⑧ AWHW xxG-SMD
Angle	±3°	⑥	Modification the cap	07.11.2012	Amy				Drawing-No.
		⑤	add soldering temperature	09.12.2011	Lucas				ASS 2316 CO
		Id.	Modification	Date	Name				

1

2

3

4

5

6

7

SV1129