



THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20  
 © COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

REVISIONS				
P	LTR	DESCRIPTION	DATE	APVD
C		REV PER ECO 08-005872	06MAR2008	CT KH



SECTION J-J

1 SEAL SLEEVE: PPS THERMOPLASTIC PER ASTM D4067, COLOR: NATURAL.  
 SEAL BOOT: FLUOROSILICONE ELASTOMER PER SAE AMS-R-25988, EXCEPT 4.6.6.1.

2. RECOMMENDED CABLES: TENSOLITE NF24Q100 OR EQUIVALENT  
 ABSI503KD24. OR EQUIVALENT

3. THIS PRODUCT IS SOLD BY TYCO CONNECTIVITY UNDER A LICENSE FROM RADIAL SA.

4 SEAL BOOT IS BONDED TO SLEEVE (1877626-2 ONLY)

5 PACKAGE ONE PER BAG AND MARK WITH BACS45E2, TE CONNECTIVITY, 00779,  
 DATE CODE AND DO NOT REMOVE FROM PACKAGE UNTIL READY FOR USE.  
 (WHEN INSPECTION REQUIRED, REPACKAGE AND RESEAL).

5	1877626-3
4	1877626-2
---	1877626-1
REMARKS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	22DEC2005	STE TE Connectivity	
DIMENSIONS:		CHK	22DEC2005	NAME	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	22DEC2005	SEAL ASSEMBLY, SIZE 8, GPR	
mm	0 PLC ±-	PRODUCT SPEC		SIZE	CAGE CODE
	1 PLC ±0.5	APPLICATION SPEC		A200779	C-1877626
	2 PLC ±0.13			SCALE	10:1
	3 PLC ±0.013	WEIGHT		SHEET	OF
	4 PLC ±0.0001			REV	C
	ANGLES ±-	CUSTOMER DRAWING			
	FINISH				
MATERIAL					