

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	11MAY2015	DW	CW
	A1	ECR-17-018349	14DEC2017	DW	CW

NOTES:

1. TECHNICAL CHARACTERISTICS:

CONTACT MATERIAL: BRASS

SURFACE PLATING:

SILVER PLATING: $\geq 2\mu\text{m}$ CONTACT RESISTANCE: $\leq 0.5\text{m}\Omega$ WIRE RANGE: 70mm^2 OPERATION TEMPERATURE: $-40\sim+125^\circ\text{C}$

注释:

1. 技术参数:

公针材料: 黄铜

表面电镀:

镀银: $\geq 2\mu\text{m}$ 接触电阻: $\leq 0.5\text{m}\Omega$ 接线范围: 70mm^2 工作温度: $-40\sim+125^\circ\text{C}$

T2060001070-000	CHM-70	CHM-70, SILVER PLATING HMN-001公针 70mm^2 , 镀银	70	22.5
PART NUMBER 料号	PART DESCRIPTION 描述		WIRE GAUGE (mm^2) 线规 (mm^2)	STRIPPING LENGTH (mm) 剥线长度 (mm)
THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 11MAY2015 David Wang		
DIMENSIONS: mm		CHK 11MAY2015 Chris Wang		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 11MAY2015 Xiang Xu	NAME CHM-70 HM PIN CONTACT	
0 PLC \pm		PRODUCT SPEC 108-137057	SIZE	
1 PLC \pm		APPLICATION SPEC 114-137057	CAGE CODE	
2 PLC \pm		WEIGHT	DRAWING NO	
3 PLC \pm		Customer Drawing	RESTRICTED TO	
4 PLC \pm			A300779	
ANGLES \pm			SCALE 2:1	
FINISH			SHEET 1 OF 1	
-			REV A1	
-				

1470-19 (3/13)