



**ST-200**

GRAY  
WIRING

TIP - CENTER CONDUCTOR  
SLEEVE - SHIELD

**ST-200**

GRAY  
WIRING

TIP - CENTER CONDUCTOR  
SLEEVE - SHIELD

**NOTES:**

1. MATERIALS:  
TIP - BRASS, NICKEL PLATED  
SLEEVE - BRASS, NICKEL PLATED  
INSULATION - PHENOLIC AND POLYESTER  
INTERNAL SHIELD - STEEL, TIN PLATED  
MOLDED HANDLE - THERMOPLASTIC, GRAY

2. THIS PRODUCT IS RoHS COMPLIANT.

**05**

**A**

\*

**05**

**X**

RoHS COMPLIANT

2ND END - ST-200

CABLE LENGTH PER TABLE BELOW

- B = 12 INCHES LONG
- C = 18 INCHES LONG
- D = 24 INCHES LONG
- F = 36 INCHES LONG
- H = 48 INCHES LONG
- K = 6 FEET LONG
- N = 10 FEET LONG
- R = 15 FEET LONG
- U = 25 FEET LONG

TYPE OF CABLE - W1000 - 1

1ST END - ST-200

**CUSTOMER DRAWING**

					<div>UNLESS OTHERWISE SPECIFIED</div> <div>1. ALL DIMENSIONS IN INCHES</div> <div>- TWO PLACE DECIMALS     ±0.02</div> <div>- THREE PLACE DECIMALS   ±0.005</div>	THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.									
						SIZE	WIDTH		MULT		LBS/M		TEMPER		
						FINISH						MATERIAL			
						SPEC No.						SPEC No.			
						FIRST USED ON				SCALE		Switchcraft®			
								1:1							
A	26124	8-9-06	JEB	TJK	DO NOT SCALE DRAWING	DATE DRAWN	BY	CHKD		APVD		SHEET    1                      OF    1			
						9-11-06	RF	RF		TJK					
REV	ECO NUMBER	DATE	BY	APVD					9-11-06		8-13-09		PART No.		REV
REVISIONS						CABLE ASSEMBLY						05A   05X			
						ST-200 TO ST-200, RoHS						A			

SolidWorks CAD File

