



**FEATURES:**

- Allows four parallel connectors to the same point.
- 3 cross .166 dia. holes
- 4.2 (.166) dia., provide side stackup connection.

**MATERIALS:**

Upper Conn.: Banana Jack  
 Material: Brass per QQ-B-626. Alloy 360 ½ Hard.  
 Finish: Nickel plated per QQ-N-290, Class 2, 200 to 300 microinches.  
 Insulation: ABS molded to Banana Jack and Banana Plug Body.  
 Color: See Tab Block  
 Marking: "POMONA ELECTRONICS 3364."

Lower Conn.: Banana Plug  
 Material: Spring – Beryllium Copper per QQ-C-533, Alloy 170, Cond. H.T.  
 Body: Same as Upper Conn.

**RATINGS:**

Operating Temperature: +50° C (+122° F) Max.  
 Operating Voltage: 5000 VDC.  
 Current: 15 Amperes Cont.  
 Contact Resistance: Less than 1 milliohm.

**ORDERING INFORMATION: Model 3364-\***

\*= Color, -0 Black, -2 Red  
 Ordering Example: 3364 -2 Color is Red

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).  
 All specifications are to the latest revisions. Specifications are subject to change without notice.  
 Registered trademarks are the property of their respective companies. Made in USA