

Product data sheet

Specifications



Telequick mounting plate for PLA enclosure H500xW500mm

NSYPMR55

Main

Range	Thalassa
Accessory / separate part category	Mounting accessory
Product or component type	Mounting plate
Device application	Multi-purpose
Enclosure nominal dimensions	-
Mounting location	Back inserts Step slide
Mounting plate description	Telequick perforated
Range compatibility	Thalassa (Thalassa PLA) Thalassa (Thalassa PHD)
Device composition	1 mounting plate
Material	Galvanised steel

Complementary

Fixing mode	By screws - screw type M8 - on back inserts location
Permanent permissible load	150 kg
Height	500 mm nominal: 370 mm real:
Width	500 mm nominal: 376 mm real:
Depth	15 mm real:
Product weight	1.4 kg
Cut-out dimensions	11 x 26 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.5 cm
Package 1 Width	37.0 cm
Package 1 Length	37.5 cm
Package 1 Weight	1.142 kg

Unit Type of Package 2	PAM
Number of Units in Package 2	150
Package 2 Height	50.0 cm
Package 2 Width	100.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	184.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)