



Aerosusa.com
service@aerosusa.com
855.393.9905

RQB45-N



Plastic connector, quick-type, bend 45°, NPT outer thread, integrated snap-in sleeve with sealing, high density. Certain sizes are UL 514B listed, see the below product details for which sizes. For installation in accordance with Article 356 of ANSI / NFPA 70, National Electric Code, NEC.

Material: PA plastics

Temperature:
-40°C ... +120°C
-40°F ... +248°F

Protection Class: IP 68 | IP 69K

Color: Black

Properties:

- Rational tubing assembly due to one-piece screw connector with push-in lock for coarse and fine profile conduits
- Simple dismounting by displacing the snap-in sleeve
- Smallest outer dimensions to be used under confined conditions
- Free of silicone, cadmium and halogen
- Self-extinguishing
- Fit for high mechanical stress
- Impact-resistant

Note:

Lock-nuts and sealing washers sold separately. See below for corresponding accessories.

CERTIFICATIONS



"Unsurspassed in Cable Protection and Strain Relief"

2409 Herr St.
Harrisburg, PA 17103



Technical Data Sheet

Aerosusa.com
service@aerosusa.com
855.393.9905

Product #	Color	Trade Size	AD	Thread	I (in)	B (in)	C (in)	E (in)	F (in)	WS (in)	lb/100	UL Listed	PU
5020.017.205	Black	3/8"	15.8	1/2 inch	0.39	0.91	0.47	1.61	1.89	0.91	2.6455		50 PC
5020.017.206	Black	1/2"	21.2	1/2 inch	0.51	1.16	0.47	2.05	2.17	1.02	3.7479	X	50 PC
5020.017.214	Black	3/4"	28.5	3/4 inch	0.67	1.46	0.51	2.68	2.68	1.22	5.7320	X	25 PC
5020.017.216	Black	1"	34.5	1 inch	0.91	1.73	0.55	2.68	2.89	1.54	8.3776	X	10 PC
5020.017.215	Black	1"	34.5	1 1/4 inch	1.14	1.73	0.55	2.87	2.89	1.77	9.9208		10 PC
5020.017.208	Black	1 1/4"	42.5	1 1/2 inch	1.18	2.05	0.67	3.19	3.23	2.28	13.8891		10 PC
5020.017.217	Black	1 1/4"	42.5	1 1/4 inch	1.42	2.05	0.67	2.99	3.15	1.85	20.5030	X	10 PC
5020.017.209	Black	1 1/2"	54.5	1 1/2 inch	1.38	2.52	0.67	3.5	3.72	2.28	19.1802	X	5 PC
5020.017.210	Black	1 1/2"	54.5	2 inch	1.77	2.58	0.67	3.74	3.76	2.72	19.8416	X	5 PC

"Unsurpassed in Cable Protection and Strain Relief"

2409 Herr St.
Harrisburg, PA 17103