



- △ ZINC.
- △ STAINLESS STEEL.
- 3. TO ASSEMBLE JACKSCREW REFER TO INSTRUCTION SHEET #1189.
- △ HOLE CENTRALLY LOCATED WITHIN ±0.07 [.003] OF THE 5.54 [.218] DIA AND THE 2.77/2.84 [.109/.112] DIA CENTER LINES.
- △ CHROMATE CONVERSION, CLEAR WITH HEXAVALENT CHROMATE.
- △ CHROMATE CONVERSION, CLEAR W/O HEXAVALENT CHROMATE.

OBSELETE	△	2.87 [.113]	201910-5
	-	2.11 [.083]	201910-3
	△	2.87 [.113]	201910-1
NOTES	A		PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN K.FOLTZ 05/26/94	Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: mm [INCHES]		CHK R.STONE 06/16/94	Tyco Electronics	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD -	NAME JACKSCREW KIT, UNASSEMBLED, FEMALE, M SERIES	
0 PLC ± -		PRODUCT SPEC	-	
1 PLC ± -		APPLICATION SPEC	-	
2 PLC ± 0.13 [.005]		SIZE	A1	
3 PLC ± -		WEIGHT	-	
4 PLC ± -		CAGE CODE	00779	
ANGLES ± -		DRAWING NO	201910	
MATERIAL JACKSCREW BODY: △	FINISH JACKSCREW BODY: SEE NOTES	RESTRICTED TO	-	
JACKSCREW TIP: △	JACKSCREW PIN: PASSIVATE	CUSTOMER DRAWING	SCALE	4:1
JACKSCREW PIN: △		SHEET	1	OF 1
		REV	L1	