



NOTE :
 - MARKING "B" IS USED TO IDENTIFY "HP" TERMINAL
 - CRIMPING SPECIFICATION ACCORDING TO AS-64322-001

2	BOX TERMINAL	STAINLESS STEEL thickness=0.15 mm	
1	BODY TERMINAL	HIGH CONDUCTIVITY COPPER ALLOY thickness=0.2 mm	
MARK	DESIGNATION	MATERIAL	

0643221339	Au 1.27μ MINI	Sn	Ni	0.75	2.5	2.4	0.6	3.3	2.8	0.75	0.119
0643221359	Au 1.27μ MINI	Sn	Ni	0.50	2.3	2.2	0.6	3.1	2.6	0.75	0.117
0643221349	Au 1.27μ MINI	Sn	Ni	0.22 to 0.44	2.0	1.7	0.6	3.1	2.6	0.75	0.112
PART NUMBER	CONTACT AREA	CRIMPING AREA	UNDERLAYER	CRIMPING RANGE (mm2)	A=0.2	B=0.2	rC+0.15 -0.1	D=0.2	E=0.2	rF±0.1	WEIGHT (g)
	PLATING										

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS	SCALE	CURRENT REV DESC: FRAME AND TITLE BLOCK UPGRADES.	
mm			
GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 613739	
ANGULAR TOL	± 2.0°	DRWN: SLAFAURE	2019/03/13
4 PLACES	± 0.1	CHK'D: SLAFAURE	2019/03/13
3 PLACES	± 0.1	APPR: SLAFAURE	2019/03/13
2 PLACES	± 0.1	INITIAL REVISION:	
1 PLACE	± 0.1	DRWN: SSUVARNA	2017/07/21
0 PLACES	± 0.1	APPR: SLAFAURE	2018/06/14
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		FIRST ANGLE PROJECTION	DRAWING SERIES
		A1-SIZE	64322
		MATERIAL NUMBER	CUSTOMER
		SEE TABLE	GENERAL MARKET
		SHEET NUMBER	1 OF 1

SD-64322-002 PSD 000 D2

PRODUCT CUSTOMER DRAWING

CP HP RCPT TRM 0.6