

# 14002-3 high SCCR barrier terminal block



**Catalog number:**

- 14002-3

**Description:**

Eaton's Bussmann series catalog number 14002-3 is a three-pole barrier terminal block featuring a high Short-Circuit Current Rating (SCCR) when protected by specific, tested upstream overcurrent protective devices (see SCCR data table for details).

**Specifications:**

**Ratings**

- Volts: 600 Vac/dc
- Amps: 115 A
- SCCR:
  - 10 kA default
  - Up to 200 kA (see SCCR data on page 2)

**Agency information**

- UL 1953 Recognized, Guide XCFR2, File E62622
- General Industry Class per UL 1059, usage Category C
- RoHS compliant



**Mechanical**

- Panel mount 3-pole configuration
- 75°C rated connectors
- Flammability: UL 94 HB

**Conductors**

Wire size (AWG)	Torque (lb-in)
2-3 Cu/Al	50
4-6 Cu/Al	45
8 Cu/Al	35
10-14 Cu	35

**Dimensions - in**



## Short-Circuit Current Rating data

The high SCCR of this block relies upon the tested, upstream overcurrent protective devices listed in this table

Catalog no.	Amps	Cu wire range line and load (AWG)	Torque lb-in (max)	(1) Cu wire range (AWG)	Max. Fuse Class and Amp*				SCCR (kA)	Min. enclosure size (in)
					LPJ	JJN, JJS	LPN-RK, LPS-RK	FRN-R, FRS-R		
14002-3	115	2 to 3 Cu/Al	50	2 to 8	200	200	100	60	200	8 x 8 x 4
		4 to 6 Cu/Al	45							
		8 Cu/Al	35	2 to 14	175	175	100	60	100	
		10 to 14 Cu	35							

\* Class G 60A (SC-60) or less or Class CC 30A (LP-CC-30, FNQ-R-30, KTK-R-30) or less are suitable for all SCCRs in this table.

The only controlled copy of this data sheet is the electronic read-only version located on the Eaton network drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

**Eaton**  
1000 Eaton Boulevard  
Cleveland, OH 44122  
Eaton.com

Bussmann Division  
114 Old State Road  
Ellisville, MO 63021  
United States  
Eaton.com/bussmannseries

© 2016 Eaton  
All Rights Reserved  
Printed in USA  
Publication No. 10614 — BU-MC16124  
October 2016

Eaton and Bussmann are valuable trademarks of Eaton in the U.S. and other countries. You are not permitted to use the Eaton trademarks without prior written consent of Eaton.

For Eaton's Bussmann series product information, call **1-855-287-7626** or visit: **Eaton.com/bussmannseries**