


CK1,6-ED-0,37ST AG

Order No.: 1663336



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1663336>

Turned 1.6 crimp contact, individual male contact, core diameter 0.14 to 0.37 mm², silver-plated

| Commercial data | |
|--------------------------|---|
| GTIN (EAN) |  4 017918 123147 |
| sales group | D090 |
| Pack | 100 pcs. |
| Customs tariff | 85366990 |
| Catalog page information | Page 528 (PC-2009) |

Product notes

WEEE/RoHS-compliant since:
12/01/2005



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

| Electrical characteristics | |
|---------------------------------|---|
| Note | For HC-M-12, HC-M-EMC, HC-D, HC-DD and VC-D contact inserts, the quality of a crimp connection is determined by DIN EN 60 352-2 |
| Ambient temperature (operation) | -40 °C ... 125 °C |

Mechanical characteristics

| | |
|---|---|
| Conductor cross-section | 0.14 mm ² ... 0.37 mm ² |
| Connection cross-section AWG | 26 ... 22 |
| Stripping length of the individual wire | 8 mm |
| Insertion/withdrawal cycles | ≥ 500 |

General characteristics

| | |
|-------------------|-------------------------|
| Type | Individual male contact |
| Series | HC-M-12 |
| Connection method | Crimp connection |

Material data

| | |
|--------------------------|--------------------|
| Contact material | Copper alloy |
| Contact surface material | hard-silver plated |

Certificates / Approvals




Certification GOST, UL

Accessories

| Item | Designation | Description |
|----------------|-------------------------|--|
| General | | |
| 1884869 | VC-EW 1,6 | Contact removal tool, for turned and rolled CK- 1.6-... contacts |
| Tools | | |
| 1676734 | CK1,6/2,5-MWZ | Assembly tool, for CK 1.6... crimp contacts for small conductor cross sections |
| 1687419 | CRIMPFOX-1,6/2,5-ED-4,0 | Crimping pliers, for turned contacts, CK 1.6 ED... and CK 2.5 ED... |

Diagrams/Drawings

Dimensioned drawing



Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;