PIN RECEPTACLES

FOR .015" - .020" DIAMETER PINS (#11 CONTACT) AND .015" - .022" DIAMETER PINS (#21 CONTACT) (SEE SPECIFIC CONTACT RANGE ON PAGE 251)

0548

0548-0-15-XX-21-XX-10-0


Solder mount in .036 min, mounting hole Also available on 16mm wide carrier tape: 1,900 parts per 13" reel See page 194.3 for Tape & Reel details

.058 DIA. .031 .085 .034 DIA .138 .155

8975

8975-0-15-XX-21-XX-10-0

Solder mount in .036 min, mounting hole Also available on 24mm wide carrier tape: 1,200 parts per 13" reel See page 194.3 for Tape & Reel details




3016

3016-0-15-XX-21-XX-10-0

Solder mount in .036 min. mounting hole Also available on 16mm wide carrier tape: 1,900 parts per 13" reel


See page 194.3 for Tape & Reel details



9548

9548-0-15-XX-21-XX-10-0

Solder mount in .036 min. mounting hole




8637

.023 DIA

HOLE

8637-0-15-XX-21-XX-10-0


Solder mount in .037 min. mounting hole Also available on 16mm wide carrier tape: 2,000 parts per 13" reel See page 194.3 for Tape & Reel details



1407

1407-0-15-XX-11-XX-10-0

Solder mount in .040 min. mounting hole Also available on 16mm wide carrier tape: 1,500 parts per 13" reel See page 194.2 for Tape & Reel details




0553/4553/8553 X553-X-15-XX-X1-XX-10-0

Also available on 16mm wide carrier tape:

1,580 parts per 13" reel

See page 194.2 for Tape & Reel details



Hex press-fit in .041 plated through-hole for Part Numbers 0553-X and 8553-0 ONLY


Hex press-fit in .042 plated through-hole for Part Number 4553-0 ONLY

Basic Part Number	Hex Dia. E	Length L	Depth N
0553-1	.044	.140	.124
0553-2	.044	.170	.154
0553-3	.044	.282	.266
4553-0	.045	.170	.154
8553-0	.044	.245	.229

0566

0566-X-15-XX-21-XX-10-0

Solder mount in .039 min. mounting hole Also available on 16mm wide carrier tape: See chart for details See page 194.3 for Tape & Reel details




Basic Part	Length	Parts per
Number	L	13" Reel
0566-1	.083	3,000
0566-2	.138	2,100

0442

0442-0-15-XX-11-XX-10-0

Solder mount in .040 min. mounting hole




0554

0554-0-15-XX-21-XX-10-0

Solder mount in .040 min, mounting hole Also available on 16mm wide carrier tape:

See page 194.3 for Tape & Reel details



SPECIFICATIONS:

Shell Material: Brass Alloy 360, 1/2 Hard

Contact Material: Beryllium Copper Alloy 172, HT

Dimensions: Inches

Tolerances On: Lengths: $\pm .005$

> Diameters: ±.002 ±2° Angles:



ORDER CODE: XXXX - X - XX - XX - XX - XX - XX - 0

BASIC PART # SPECIFY SHELL FINISH:

 $\textbf{01} \ \ 200 \ \mu '' \ \text{TIN/LEAD OVER NICKEL}$

- 80 200 μ" TIN OVER NICKEL (RoHS)
- ◆ 15 10 μ" GOLD OVER NICKEL (RoHS)

SPECIFY CONTACT FINISH:

- **02** 100 μ " TIN/LEAD OVER NICKEL
- 84 100 μ" TIN OVER NICKEL (RoHS)
- 27 30 μ" GOLD OVER NICKEL (RoHS)

SELECT CONTACT:

#11 or #21 CONTACT (DATA ON PAGE 251)

(For alternate contact choices, see group A on page 248)

