



Recommended P.C.B. Layout (Top View)
Tolerances: $\pm 0.10\text{mm}$

Position	A	B	C	D
9F	16.30	25.00	30.8	19.2
15F	24.60	33.30	39.2	27.7
25F	38.30	47.10	53.1	41.1
37F	54.80	63.50	69.4	57.3
50F	52.20	61.00	67.00	55.10

Specification:

Material:
Insulator: PBT, rated UL94V-0
Contacts: Brass
Shell: Steel
Rivet, Boardlock: Copper Alloy

Contact Plating:

Gold Flash over 50u"nickel

Electrical

Operation Voltage: 250 VAC max.
Current Rating: 3 Amps max.
Contact Resistance: 15 mohms max.
Insulation Resistance: 3000 Mohms min @ 500 VDC
Dielectric Withstanding Voltage: 1000 VAC/minute
Operating Temperature: -55°C to $+105^{\circ}\text{C}$

Scale	1:1						Name	Item No. A-DFxxPP-TAXM-B-R
TOLERANCE					Drawn	11.16.11	Chappell	
X.X	± 0.40				Approved			Title D-Sub Solder
X.XX	± 0.25							Drawing No.
X.XXX	± 0.15							rev00
Angle	$\pm 3^{\circ}$							
								Replace
								Sheet
			Modification	Date	Name			

