

2-1376382-3 ✓ ACTIVE




Power Key 5.0

TE Internal #: 2-1376382-3

Rectangular Power Connectors, Header, Receptacle, Wire-to-Board, 2 Position, 5 mm [.197 in] Centerline, Printed Circuit Board, UL 94V-0, Power Key 5.0

[View on TE.com >](#)

Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors > STD Temp Power Key Header



Rectangular Power Connector Type: **Header**

Connector & Housing Type: **Receptacle**

Connector System: **Wire-to-Board**

Number of Positions: **2**

Centerline (Pitch): **5 mm [.197 in]**

[All STD Temp Power Key Header \(18\)](#)

Features

Product Type Features

Header Type	Fully Shrouded
Rectangular Power Connector Type	Header
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	2
PCB Mount Orientation	Vertical
Number of Power Positions	2
Number of Rows	1

Electrical Characteristics



Operating Voltage	300 VAC
-------------------	---------

Contact Features

Mating Post Length	6.3 mm[.248 in]
--------------------	-----------------

PCB Contact Termination Area Plating Material Thickness	1 μ m[39.37 μ in]
---	---------------------------

Contact Layout	Inline
----------------	--------

Contact Mating Area Plating Material	Tin
--------------------------------------	-----

Contact Base Material	Copper Alloy
-----------------------	--------------

Contact Current Rating (Max)	10 A
------------------------------	------

Contact Retention Within Housing	Without
----------------------------------	---------

Contact Type	Tab
--------------	-----

PCB Contact Termination Area Plating Material	Tin
---	-----

Contact Mating Area Plating Material Thickness	39.36 μ m[1 μ in]
--	---------------------------

Termination Features

Termination Post & Tail Length	3.5 mm[.138 in]
--------------------------------	-----------------

Termination Method to Printed Circuit Board	Through Hole - Press-Fit
---	--------------------------

Mechanical Attachment

Mating Retention	With
------------------	------

Mating Alignment	Without
------------------	---------

PCB Mount Alignment	Without
---------------------	---------

PCB Mount Retention	With
---------------------	------

PCB Mount Retention Type	Mounting Post/Kinked Legs
--------------------------	---------------------------

Mating Retention Type	Latch
-----------------------	-------

Connector Mounting Type	Board Mount
-------------------------	-------------

Housing Features

Centerline (Pitch)	5 mm[.197 in]
--------------------	---------------

Housing Color	Blue
---------------	------

Housing Material	Nylon 6/6 GF
------------------	--------------

Dimensions

Connector Height	14.1 mm[.55 in]
------------------	-----------------

PCB Thickness (Recommended)	.06 mm[1.6 in]
-----------------------------	----------------

Product Width	14.1 mm[.555 in]
---------------	------------------

Product Length	11.6 mm[.456 in]
----------------	------------------



Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

CSA Rating	LR 7189
UL Rating	Recognized
Agency/Standard	CSA, UL
Approved Standards	UL E28476
UL Flammability Rating	UL 94V-0
Glow Wire Rating	Standard Part - Not Glow Wire

Packaging Features

Packaging Quantity	100
Packaging Method	Bag

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides

on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 2-1376388-3
5MM POWER KEY 2P PLUG HSG BLUE




TE Part # 1376394-1
5MM POWER KEY D/L PLATE GREEN



TE Part # CAT-P8704-H342A
Glow Wire Power Key Header


Also in the Series | Power Key 5.0



Insertion & Extraction Tools(1)



PCB Latches, Locks & Retainers(4)



Power Contacts(4)




Rectangular Power Connectors(107)

Customers Also Bought



TE Part #179838-1
AMP POWER D/LOCK T/HDR ASSY 2P



TE Part #2-1376388-3
5MM POWER KEY 2P PLUG HSG BLUE



TE Part #1376382-1
5mm B-T-W Conn. 2P HDR ASSEMBL



TE Part #1376383-1
5mm B-T-W Conn. 3P HDR ASSEMBL



TE Part #179840-6
AMP POWER D/LOCK T/HDR ASSY 4P



TE Part #1827392-1
GIC 3.3 HDR ASSY 6P



TE Part #1827391-1
GIC 3.3 HDR ASSY 4P



TE Part #3-1971906-3
HEADER ASSY 6POS,KEYING-C,NEW GIC3.3



Documents

Product Drawings

5mm B-T-W Conn. 2P HDR ASSEMBL

English

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_2-1376382-3_D.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2-1376382-3_D.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2-1376382-3_D.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[SOFT_SHELL_PIN_SOCKET_CONNECTORS_STANDARD_DENSITY](#)

English

[1-1773881-9 Power Key Connector Quick Reference Guide](#)

English

Product Specifications

[5.0 POWER KEY CONNECTOR](#)

Japanese

[Application Specification](#)

Japanese

Product Environmental Compliance

[MD_2-1376382-3_052420152334_dmtec](#)

English

[MD_2-1376382-3_052420152334_dmtec](#)

English



[Agency Approvals](#)

[VDE Certificate](#)

English