
3M[™] MetPak[™] 2-FB Inverse Header

2 mm 5-Row, Right Angle, Solder Tail





- Three levels of early mate, late break (EMLB)
- sequencing or selective loading options
- Footprint compatible with standard Futurebus+®
- Solder tail with true-position wafer
- Ideal for hot swapping applications
- End-to-end stackable
- · Right angle male for daughter card
- Mates with MP2-R for backplane applications and MP2-SXXXG for coplanar applications
- RoHS Compliant. See the Regulatory Information Appendix (RIA) in the "RoHS compliance" section of www.3Mconnectors.com for compliance information (RIA E1 & C1 apply)

Date Modified: September 17, 2013

TS-1122-C Sheet 1 of 4

Physical

Insulation:

Material: High Temp LCP Flammability: UL 94V-0 Color: Beige

Contact:

Material: Copper Alloy

Plating:

Underplating: 50 μ" [1.27 μm] Nickel Wiping Area: See Ordering Information Solder Tails: See Ordering Information

Electrical

Current Rating: Signal: 1.5 A – All contacts simultaneously

Insulation Resistance: $10^3 M\Omega$ Withstanding Voltage: $1000 V_{AC}$

Environmental

Temperature Rating: -55°C to +125°C

Process Temperature Rating: 260°C (Profile per J-STD-020C)

Moisture Sensitivity Level: 1 (per J-STD-020C)

MetPak is a trademark of 3M Company.

Futurebus+ is a registered trademark of the Institute of Electrical and Electronic Engineers, Inc. (IEEE)

UL File No.: E68080

2 mm 5-Row, Right Angle, Solder Tail

MP2 Series




Table 1 - Connector & Row Lengths						
Pin Count	Dim. "A" mm [inch]	Dim "B" mm [inch]	Rows			
030	11.95 [0.471]	10.00 [0.394]	5			
060	23.95 [0.943]	22.00 [0.866]	5			
090	35.95 [1.415]	34.00 [1.339]	5			
120	47.95 [1.889]	46.00 [1.811]	5			
150	59.95 [2.36]	58.00 [2.283]	5			
180	71.95 [2.833]	70.00 [2.756]	5			
210	83.95 [3.305]	82.00 [3.228]	5			
240	95.95 [3.778]	94.00 [3.701]	5			
270	107.95 [4.251]	106.00 [4.173]	5			
300	119.95 [4.722]	118.00 [4.646]	5			
420	167.95 [6.612]	166.00 [6.535]	5			

Table 2 - Mate & Tail Lengths, mm vs. Loading Pattern											
Loading Pattern Code	Description	Mate Length Row A	Mate Length Row B	Mate Length Row C	Mate Length Row D	Mate Length Row E	Tail Length Row A	Tail Length Row B	Tail Length Row C	Tail Length Row D	Tail Length Row E
1	All Positions Filled	5.00	5.00	5.00	5.00	5.00	3.30	3.30	3.30	3.30	3.30
2	All Positions Filled	4.25	5.00	5.00	5.00	5.00	4.05	3.30	3.30	3.30	3.30
3	All Positions Filled	3.50	4.25	4.25	5.00	5.00	4.80	4.05	4.05	3.30	3.30
4	All Positions Filled	4.25	5.00	4.25	4.25	4.25	4.05	3.30	4.05	4.05	4.05
5	Rows A, B, C and D Filled	5.00	5.00	5.00	5.00	NA	3.30	3.30	3.30	3.30	NA
6	Rows A, B, C and D Filled	5.00	4.25	4.25	5.00	NA	3.30	4.05	4.05	3.30	NA
7	All Positions Filled	4.25	5.00	4.25	5.00	4.25	4.05	3.30	4.05	3.30	4.05
8	All Positions Filled	4.25	4.25	4.25	4.25	4.25	4.05	4.05	4.05	4.05	4.05
9	All Positions Filled	5.00	3.50	3.50	3.50	4.25	3.30	4.80	4.80	4.80	4.05
Α	All Positions Filled	3.75	4.50	5.25	4.50	3.75	4.55	3.80	3.05	3.80	4.55
В	All Positions Filled	3.75	4.50	3.75	4.50	3.75	4.55	3.80	4.55	3.80	4.55
С	All Positions Filled	5.75	5.75	5.75	5.75	5.75	2.55	2.55	2.55	2.55	2.55
D	All Positions Filled	4.25	5.00	5.75	5.00	4.25	4.05.	3.30	2.55	3.30	4.05
E	All Positions Filled	5.00	5.75	5.75	5.75	5.00	4.05	4.05	4.05	4.05	4.05
G	Rows A, B, C and D Filled	5.00	4.25	4.25	5.00	NA	3.30	4.05	4.05	3.30	NA

Table 3 - Plating						
Plating Suffix	x Plating Composition					
KR (RIA E1 & C1 apply)	0.76 μm [30 μ"] Min. Au Contact Area					
	2.54 μm [100 μ"] Min. Matt Whisker Mitigating Sn Tail Area					
	1.27 μm [50 μ"] Min. Ni all over					
LR (RIA E1 & C1 apply)	0.08 μm [3 μ"] Min. Au Contact Area					
	0.67 μm [27 μ"] Min. PdNi Contact Area					
	$2.54~\mu m$ [100 $\mu"$] Min. Matt Whisker Mitigating Sn Tail Area					
	1.27 μm [50 μ"] Min. Ni all over					

TS-1122-C Sheet 3 of 4





Table 4 - HOLE PLATING FINISHES							
HOLE	OLE Finished Dia. Cu Thickness [mm [in]		Immersion Matte Sn Thickness microns [µ"] Electrolytic Au Thickness microns [µ"]		OSP ENTEK Thickness microns [µ"]	Drilled Hole Dia. mm [in]	
"D"	0.700-0.800 [.02760315]	0.025-0.045 [0.001-0.002]	0.5 - 2.5 [20 - 100]	0.1 - 0.5 [4 - 20]	0.2 - 0.5 [8 - 20]	0.830-0.860 [.0330- .0340] or 0.85 mm [#66] TWIST DRILL	



3M is a trademark of 3M Company.

Important Notice

Warranty; Limited Remedy; Limited Liability.

unless expressly agreed upon, in writing, by an authorized officer of 3M.

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect



3M Electronics Solutions Division 6801 River Place Blvd. Austin, TX 78726-9000 U.S.A. 1-800-225-5373 www.3Mconnectors.com