



PCE-DD-D Hardness tester

PCE-DD-D is a Shore D durometer or hardness tester used to measure the Shore hardness of materials such as hard rubber, hard resin, acrylic, glass, thermoplastic and more. This Shore D hardness tester uses an impact rod with a 30° conical point and 50 Newtons (N) of force to make a surface indentation on material samples with a minimum thickness of 6 mm or 0.24 in. (Note: If a material sample does not meet the minimum thickness required, the sample should be reinforced on the back with more of the same material.)

- ▶ For Shore D hardness testing
- ▶ Ideal for use with hard rubber, hard resin, acrylic, glass, thermoplastic, etc.
- ▶ Handheld, portable, digital measuring device
- Measurement range: 0 ... 100 Shore D
- Accuracy: ± 2 Hardness Grade
- Large, easy-to-read display
- Hold functionality





www.pce-instruments.com

Specifications

Measurement range	0 100 Shore D
Resolution	0.5 Hardness - Grade
Accuracy	± 2 Hardness - Grade
Depth of indentation	0.0 2.5 mm / 0.0 0.01 in
Pressure force	5 kg / 11.02 lbs
Indenter	30°
Dimensions	85 mm x 60 mm x 25 mm / 3.3 in x 2.36 in x 0.4 in
Power supply	1 x 1.5V (SR44)
Weight	300 g / < 1 lb

More information







www.pce-instruments.com