



**Notes:**

1. Electrical Specifications:
  - Meets USB 2.0 Specification
  - Contact Resistance: 30 mOhm max.
  - Insulation Resistance: 1000 MOhm min. @ 100 VDC
  - Current Rating: 1.5 A max. at 25°C
  - Working Voltage: 30 V (RMS) max.
  - DWV: 500 VAC/60s at sea Level
  - Operating Temperature: -40°C to +85°C
2. Material and Finish:
  - Metal Coupling Ring: Brass, Nickel Plated
  - Plug Housing: ABS, Nickel Plated, UL94 V-0
  - Interfacial Seal: Silicon, Color: White
  - Cable Fitting: PA (Black), UL94 V-0
  - Cable Fitting Rubber Ring: NBR, Color: Black
  - USB Metal Shell: SPCC, Nickel Plated
  - USB Insulator: PBT UL94 V-0
  - USB Contacts: Copper Alloy,
  - USB Contact Finish: 30 u" Gold min. over Nickel for mating area, Tin over Nickel for solder cup
3. USB Type A Plug accepts AWG28 to AWG24 wires, Cable OD of 4.0 mm to 5.5 mm
4. IP67 rated when fully mated with the appropriate mating connector

RoHS Compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION. <b>DO NOT ALTER CAD DRAWING BY HAND</b>				Customer:			Tolerance Unless otherwise specified		 Autodesk Inventor	Scale: 1.5:1	Dim. in mm
				Name	Title	Approval Date	2008	Date		Name	Material: See Notes
g	1 x g	Apr/21/2017	Vincent Ke	2008	Date	Name	Title: IP67 USB 2.0 Type A Plug (Solder Cup) Assembly Kit Metal Version	Drawing No.: 17K1A115	DIN A3		
f	1 x f	Apr/21/2017	Vincent Ke	Draw.	Oct. 31	Vincent Ke					
e	1 x e	Feb/23/2017	Vincent Ke	Appd.	Oct. 31	J. Chaudry	Part No.: 17-200331	Sheet 1/1			
d	1 x d	Jun/23/2014	Vincent Ke	Norm							
c	1 x c	Nov/26/2009	Vincent Ke	D-old							
b	1 x b	Jun/01/2009	Vincent Ke								
a	original										
Rev.	Changes	Date	Name	<b>CONEC</b>							