


In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		OPERATING TEMPERATURE RANGE		STORAGE TEMPERATURE RANGE	
		-25°C TO +85°C		-25°C TO +60°C	
RATING					
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS		QT	AT
CONSTRUCTION		VISUALLY AND BY MEASURING INSTRUMENT.		X	X
GENERAL EXAMINATION		ACCORDING TO DRAWING.			
MECHANICAL CHARACTERISTICS					
VIBRATION	FREQUENCY 10 TO 55 Hz SINGLE AMPLITUDE 0.75 mm, 5 min/CYCLE, TOTAL 10 CYCLES.	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-
SHOCK	490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.			X	-
ENVIRONMENTAL CHARACTERISTICS					
THERMAL SHOCK	TEMP -55 →+5 TO +35 →+85 →+5 TO +35 °C TIME 30 → 5 → 30 → 5 min. UNDER 5 CYCLES.	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-
CORROSION SALT MIST	EXPOSED AT 5 % SALT WATER, FOR 48 h.	NO HEAVY CORROSION THAT LOSE FUNCTION.		X	-
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
△					
REMARK					
1 EXAMINATION IS HELD WITH "DH60- * * P".					
Unless otherwise specified, refer to JIS C 5402 .		APPROVED		A0. SUZUKI	09. 04. 27
		CHECKED		MO. SHIMOYAMA	09. 04. 24
		DESIGNED		TS. ITO	09. 04. 24
		DRAWN		TS. ITO	09. 04. 24
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.		ELC4-126895-00	
		SPECIFICATION SHEET		DH-LNA	
		HIROSE ELECTRIC CO., LTD.		CODE NO.	CL244-0045-0-00
		PART NO.			1/1