



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to IEC 61169-50

Documents

Assembly instruction 28 D1

Material and plating

Connector parts

| | |
|------------------|---------------|
| Center contact | Brass |
| Outer contact | Spring bronze |
| Body | Brass |
| Dielectric | PTFE |
| Unlocking sleeve | Brass |
| Crimping ferrule | Copper |

Plating

| |
|--|
| AuroDur®, gold plated |
| White bronze(e.g. Optalloy®) |
| Flash white bronze over silver(e.g. Optargen®) |
| White bronze(e.g. Optalloy®) |
| Flash white bronze over silver(e.g. Optargen®) |

Electrical data

| | |
|-------------------------------------|--|
| Impedance | 50 Ω |
| Frequency | DC to 18 GHz |
| Return loss | ≥ 29 dB, DC to 3 GHz ≥ 25 dB, 3 to 4 GHz ≥ 23 dB, 4 to 6 GHz |
| Insertion loss | ≤ 0.05 x √f(GHz) dB, DC to 6 GHz |
| Insulation resistance | ≥ 5 x10 ³ MΩ |
| Center contact resistance | ≤ 3 mΩ |
| Outer contact resistance | ≤ 2.5 mΩ |
| Test voltage, at sea level, 50Hz | 1000 V rms |
| Working voltage, at sea level, 50Hz | 480 V rms |
| RF-leakage | ≥ 95 dB up to 2 GHz ≥ 80 dB up to 4 GHz ≥ 70 dB up to 6 GHz |

- Limitations are possible due to the used cable type -

Mechanical data

| | |
|-----------------------------------|-----------|
| Mating cycles | min. 100 |
| Center contact captivation: axial | ≥ 20 N |
| Engagement force | typ. 25 N |
| Disengagement force | typ. 20 N |
| Retention force for interface | 60 N min. |

Environmental data

| | |
|-------------------------|--------------------------------|
| Temperature range | -40°C to +85°C |
| Storage temperature | -40°C to +85°C |
| Thermal shock | IEC 60169-1 16.4 (-40 / +85°C) |
| Corrosion | IEC 60169-1 16.7 (48 hrs) |
| Vibration | IEC 60068-2-64 random |
| Damp heat, steady state | IEC 60169-1 16.3 (96 hrs) |
| RoHS | compliant |

Tooling

| | |
|---------------|------------|
| Crimping tool | 11W150-000 |
| Crimp insert | 11W150-108 |

Suitable cables

RG 142 B/U, RG 223 /U, RG 400 /U

Weight

| | |
|--------|-----------|
| Weight | 6.0 g/pce |
|--------|-----------|

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

For the installation of the electrotechnical equipment, particular electrotechnical expertise is required.



Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/09.14/6.2

| | | | | | | | |
|--|----------|-------------|----------|------|--|----------------|---------------|
| Draft | Date | Approved | Date | Rev. | Engineering change number | Name | Date |
| Inge Mühlauer | 05.10.04 | Chr. Janßen | 03.11.20 | h00 | 20-1927 | S. Huber-Siegl | 03.11.20 |
| Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de | | | | | Tel. : +49 8684 18-0 Email : info@rosenberger.de | | Page 2 / 2 |