

Female connector - RC/TGGM/KVD/LBL 16+3 - 1685505


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Socket M23, 19-pos., straight, shielded, freely configurable, with solder connection, for external cable diameter 9.5 mm ... 14.5 mm



Key commercial data

Packing unit	1 PCE
GTIN	 4 017918 878900
Custom tariff number	85366990
Country of origin	GERMANY

Technical data

General data

Rated voltage	150 V
Total rated current	10 A (with 1 mm ² conductor cross section)
Number of positions	19
Degree of protection	IP65
Degree of protection	IP67
Ambient temperature (operation)	-20 °C ... 125 °C

Master cable data

Connection method	M23 screw locking
Conductor cross section max. (signal)	1 mm ²
Conductor cross section max. (energy)	1.5 mm ²
External cable diameter min.	9.5 mm
External cable diameter max.	14.5 mm

Insulation material

Female connector - RC/TGGM/KVD/LBL 16+3 - 1685505

Technical data

Insulation material

Housing material	GD-Zn
Housing surface material	Nickel-plated
Contact material	CuZn
Contact surface material	Gold-plated
Contact carrier material	PBT
Sealing material	FPM

Connection assignment

Slot/position = pin = conductor color	1 / 4 (A) = 15 = WH
Slot/position = pin = conductor color	1 / 2 (B) = 7 = GY/PK
Slot/position = pin = conductor color	2 / 4 (A) = 5 = GN
Slot/position = pin = conductor color	2 / 2 (B) = 4 = RD/BU
Slot/position = pin = conductor color	3 / 4 (A) = 16 = YE
Slot/position = pin = conductor color	3 / 2 (B) = 8 = WH/GN
Slot/position = pin = conductor color	4 / 4 (A) = 3 = GY
Slot/position = pin = conductor color	4 / 2 (B) = 14 = BN/GN
Slot/position = pin = conductor color	5 / 4 (A) = 17 = PK
Slot/position = pin = conductor color	5 / 2 (B) = 9 = WH/YE
Slot/position = pin = conductor color	6 / 4 (A) = 2 = RD
Slot/position = pin = conductor color	6 / 2 (B) = 13 = YE/BN
Slot/position = pin = conductor color	7 / 4 (A) = 11 = BK
Slot/position = pin = conductor color	7 / 2 (B) = 10 = WH/GY
Slot/position = pin = conductor color	8 / 4 (A) = 1 = VT
Slot/position = pin = conductor color	8 / 2 (B) = 18 = GY/BN
Slot/position = pin = conductor color	1-8 / 1 (+ 120 V) = 19 = BN
Slot/position = pin = conductor color	1-8 / 3 (0 V) = 6 = BU
Slot/position = pin = conductor color	1-8 / 5 (PE) = 12 = GN/YE

Classifications

ETIM

ETIM 2.0	EC000437
ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000437

UNSPSC

UNSPSC 11	31261502
-----------	----------

Female connector - RC/TGGM/KVD/LBL 16+3 - 1685505

Classifications

UNSPSC

UNSPSC 12.01	31261502
UNSPSC 13.2	31261502
UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27261203
eCl@ss 7.0	27440202

Approvals

Approvals


Approvals

GOST / GOST

Ex Approvals

Approvals submitted

Approval details



Accessories

Accessories

Female connector - RC/TGGM/KVD/LBL 16+3 - 1685505

Accessories

Pipe spanner - PLUSCON-RCS - 1665062



Special pipe spanner, tool for mounting the M23 connector housing (with assembly), for coupling and sleeve housing

Drawings

Schematic diagram



Pin assignment M23 socket, 19-pos., female side view

Female connector - RC/TGGM/KVD/LBL 16+3 - 1685505

Dimensioned drawing

