



POLE	MATERIAL NUMBER	ENGINEERING NUMBER
3	1200905001	4R3H400013
4	1200310118	4R4H400013

CONNECTOR SPECIFICATION:	
VOLTAGE RATING	3-4POL:60V/AC 75V/DC
AMPERAGE RATING	3 AMPS
PROTECTION	IP67
OPERATING TEMPERATURE	-25°C TO +90°C

ITEM	COMPONENT	MATERIAL	FINISH
1	INSERT	POLYURETHANE (PUR)	BLACK
2	CONTACT SOCKET	COPPER ALLOY	GOLD OVER NICKEL
3	SHELL	BRASS	NICKEL PLATED
4	LOCKNUT	BRASS	NICKEL PLATED
5	O-RING	FPM	RED
6	O-RING	VITON	BLACK

DESCRIPTION EC NO: WEU2010-0338 DRWN: REISSNER 2010/02/15 CHK'D: RE APPR: FPACHER 2010/02/24 REV 1	QUALITY SYMBOLS ▽ = 0 ∇ = 0	GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ±--- ±--- 3 PLACES ±--- ±--- 2 PLACES ±--- ±--- 1 PLACE ±0.1 ±--- ANGULAR ± --- °	DIMENSION STYLE MM DRAWN BY DATE REISSNER 2010/02/15 CHECKED BY DATE FP 2010/02/15 APPROVED BY DATE FPACHER 2010/02/19	SCALE 2:1 DESIGN UNITS METRIC THIRD ANGLE PROJECTION	NC-XP-FE/FE REC-PG7 PCB MOUNT MOLEX INCORPORATED DOCUMENT NO. SD-120090-012 SHEET NO. 1 OF 1	
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE TABLE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
	SIZE A3					