

NLAS325

Dual SPST Analog Switch, Low Voltage, Single Supply

The NLAS325 is a dual SPST (Single Pole, Single Throw) switch, similar to 1/2 a standard 4066. The device permits the independent selection of 2 analog/digital signals. Available in the Ultra-Small 8 package.

The use of advanced 0.6 μ CMOS process, improves the R_{ON} resistance considerably compared to older higher voltage technologies.

Features

- On Resistance is 20 Ω Typical at 5.0 V
- Matching is < 1.0 Ω Between Sections
- 2.0–6.0 V Operating Range
- Ultra Low < 5.0 pC Charge Injection
- Ultra Low Leakage < 1.0 nA at 5.0 V, 25°C
- Wide Bandwidth > 200 MHz, –3.0 dB
- 2000 V ESD (HBM)
- R_{ON} Flatness $\pm 6.0 \Omega$ at 5.0 V
- Independent Enables; One Positive, One Negative
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant




Figure 1. Pinout



ON Semiconductor®

www.onsemi.com

MARKING DIAGRAM



A9 = Device Code
M = Date Code*
▪ = Pb-Free Package

(Note: Microdot may be in either location)

PIN ASSIGNMENT

| | |
|---|-----------------|
| 1 | NO1 |
| 2 | COM1 |
| 3 | IN2 |
| 4 | GND |
| 5 | NC2 |
| 6 | COM2 |
| 7 | IN1 |
| 8 | V _{CC} |

FUNCTION TABLE

| On/Off Enable Input | Analog Switch 1 | Analog Switch 2 |
|---------------------|-----------------|-----------------|
| L | Off | On |
| H | On | Off |

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 9 of this data sheet.

NLAS325

MAXIMUM RATINGS

| Symbol | Parameter | Value | Unit |
|------------------|---|------------------------|------|
| V _{CC} | DC Supply Voltage | -0.5 to +7.0 | V |
| V _I | DC Input Voltage | -0.5 to +7.0 | V |
| V _O | DC Output Voltage | -0.5 to +7.0 | V |
| I _{IK} | DC Input Diode Current V _I < GND | -50 | mA |
| I _{OK} | DC Output Diode Current V _O < GND | -50 | mA |
| I _O | DC Output Sink Current | ±50 | mA |
| I _{CC} | DC Supply Current per Supply Pin | ±100 | mA |
| I _{GND} | DC Ground Current per Ground Pin | ±100 | mA |
| T _{STG} | Storage Temperature Range | -65 to +150 | °C |
| T _L | Lead Temperature, 1.0 mm from Case for 10 Seconds | 260 | °C |
| T _J | Junction Temperature under Bias | +150 | °C |
| θ _{JA} | Thermal Resistance (Note 1) | 250 | °C/W |
| P _D | Power Dissipation in Still Air at 85°C | 250 | mW |
| MSL | Moisture Sensitivity | Level 1 | |
| F _R | Flammability Rating Oxygen Index: 28 to 34 | UL 94 V-0 @ 0.125 in | |
| V _{ESD} | ESD Withstand Voltage Human Body Model (Note 2) Machine Model (Note 3) Charged Device Model (Note 4) | > 2000 > 200 N/A | V |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Measured with minimum pad spacing on an FR4 board, using 10 mm-by-1 inch, 2-ounce copper trace with no air flow.
2. Tested to EIA/JESD22-A114-A.
3. Tested to EIA/JESD22-A115-A.
4. Tested to JESD22-C101-A.

RECOMMENDED OPERATING CONDITIONS

| Symbol | Parameter | Min | Max | Unit |
|---------------------------------|---|-----|-----------------|------|
| V _{CC} | DC Supply Voltage | 2.0 | 5.5 | V |
| V _{IN} | Digital Select Input Voltage | GND | 5.5 | V |
| V _{IS} | Analog Input Voltage (NC, NO, COM) | GND | V _{CC} | V |
| T _A | Operating Temperature Range | -55 | +125 | °C |
| t _r , t _f | Input Rise or Fall Time, SELECT V _{CC} = 3.3 V ± 0.3 V V _{CC} = 5.0 V ± 0.5 V | 0 | 100 20 | ns/V |

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

DEVICE JUNCTION TEMPERATURE VERSUS TIME TO 0.1% BOND FAILURES

| Junction Temperature °C | Time, Hours | Time, Years |
|-------------------------|-------------|-------------|
| 80 | 1,032,200 | 117.8 |
| 90 | 419,300 | 47.9 |
| 100 | 178,700 | 20.4 |
| 110 | 79,600 | 9.4 |
| 120 | 37,000 | 4.2 |
| 130 | 17,800 | 2.0 |
| 140 | 8,900 | 1.0 |




Figure 2. Failure Rate vs. Time Junction Temperature

NLAS325

DC CHARACTERISTICS – Digital Section (Voltages Referenced to GND)

| Symbol | Parameter | Condition | V _{CC} | Guaranteed Limit | | | Unit |
|-----------------|---|---|-----------------|------------------|-------|--------|------|
| | | | | –55°C to 25°C | <85°C | <125°C | |
| V _{IH} | Minimum High-Level Input Voltage, Select Inputs | | 2.0 | 1.5 | 1.5 | 1.5 | V |
| | | | 2.5 | 1.9 | 1.9 | 1.9 | |
| | | | 3.0 | 2.1 | 2.1 | 2.1 | |
| | | | 4.5 | 3.15 | 3.15 | 3.15 | |
| | | | 5.5 | 3.85 | 3.85 | 3.85 | |
| V _{IL} | Maximum Low-Level Input Voltage, Select Inputs | | 2.0 | 0.5 | 0.5 | 0.5 | V |
| | | | 2.5 | 0.6 | 0.6 | 0.6 | |
| | | | 3.0 | 0.9 | 0.9 | 0.9 | |
| | | | 4.5 | 1.35 | 1.35 | 1.35 | |
| | | | 5.5 | 1.65 | 1.65 | 1.65 | |
| I _{IN} | Maximum Input Leakage Current, Select Inputs | V _{IN} = 5.5 V or GND | 0 V to 5.5 V | ±0.2 | ±2.0 | ±2.0 | μA |
| I _{CC} | Maximum Quiescent Supply Current | Select and V _{IS} = V _{CC} or GND | 5.5 | 4.0 | 4.0 | 8.0 | μA |

DC ELECTRICAL CHARACTERISTICS – Analog Section

| Symbol | Parameter | Condition | V _{CC} | Guaranteed Limit | | | Unit |
|--|---|--|-----------------|------------------|-------|--------|------|
| | | | | –55°C to 25°C | <85°C | <125°C | |
| R _{ON} | Maximum “ON” Resistance (Figures 16 – 22) | V _{IN} = V _{IL} or V _{IH} V _{IS} = GND to V _{CC} I _{IN} ≤ 10 mA | 2.5 | 85 | 95 | 105 | Ω |
| | | | 3.0 | 45 | 50 | 55 | |
| | | | 4.5 | 30 | 35 | 40 | |
| | | | 5.5 | 25 | 30 | 35 | |
| R _{FLAT(ON)} | ON Resistance Flatness (Figures 16 – 22) | V _{IN} = V _{IL} or V _{IH} I _{IN} ≤ 10 mA V _{IS} = 1.0 V, 2.0 V, 3.5 V | 4.5 | 4.0 | 4.0 | 5.0 | Ω |
| I _{NC(OFF)} I _{NO(OFF)} | NO or NC Off Leakage Current (Figure 8) | V _{IN} = V _{IL} or V _{IH} V _{NO} or V _{NC} = 1.0 V _{COM} 4.5 V | 5.5 | 1.0 | 10 | 100 | nA |
| I _{COM(ON)} | COM ON Leakage Current (Figure 8) | V _{IN} = V _{IL} or V _{IH} V _{NO} 1.0 V or 4.5 V with V _{NC} floating or V _{NO} 1.0 V or 4.5 V with V _{NO} floating V _{COM} = 1.0 V or 4.5 V | 5.5 | 1.0 | 10 | 100 | nA |

NLAS325

AC ELECTRICAL CHARACTERISTICS (Input $t_r = t_f = 3.0$ ns)

| Symbol | Parameter | Test Conditions | V_{CC} (V) | V_{IS} (V) | Guaranteed Maximum Limit | | | | | | Unit | |
|-----------|--------------------------------------|---|-----------------|-----------------|--------------------------|------|-----|--------|-----|---------|------|-----|
| | | | | | -55°C to 25°C | | | < 85°C | | < 125°C | | |
| | | | | | Min | Typ* | Max | Min | Max | Min | | Max |
| t_{ON} | Turn-On Time (Figures 11 and 12) | $R_L = 300 \Omega$, $C_L = 35$ pF (Figures 4 and 5) | 2.5 | 2.0 | 5.0 | 23 | 35 | 5.0 | 38 | 5.0 | 41 | ns |
| | | | 3.0 | 2.0 | 5.0 | 16 | 24 | 5.0 | 27 | 5.0 | 30 | |
| | | | 4.5 | 3.0 | 2.0 | 11 | 16 | 2.0 | 19 | 2.0 | 22 | |
| | | | 5.5 | 3.0 | 2.0 | 9.0 | 14 | 2.0 | 17 | 2.0 | 20 | |
| t_{OFF} | Turn-Off Time (Figures 11 and 12) | $R_L = 300 \Omega$, $C_L = 35$ pF (Figures 4 and 5) | 2.5 | 2.0 | 1.0 | 7.0 | 12 | 1.0 | 15 | 1.0 | 18 | ns |
| | | | 3.0 | 2.0 | 1.0 | 5.0 | 10 | 1.0 | 13 | 1.0 | 16 | |
| | | | 4.5 | 3.0 | 1.0 | 4.0 | 6.0 | 1.0 | 9.0 | 1.0 | 12 | |
| | | | 5.5 | 3.0 | 1.0 | 3.0 | 5.0 | 1.0 | 8.0 | 1.0 | 11 | |
| t_{BBM} | Minimum Break-Before-Make Time | $V_{IS} = 3.0$ V (Figure 3) $R_L = 300 \Omega$, $C_L = 35$ pF | 2.5 | 2.0 | 1.0 | 12 | | 1.0 | | 1.0 | | ns |
| | | | 3.0 | 2.0 | 1.0 | 11 | | 1.0 | | 1.0 | | |
| | | | 4.5 | 3.0 | 1.0 | 6.0 | | 1.0 | | 1.0 | | |
| | | | 5.5 | 3.0 | 1.0 | 5.0 | | 1.0 | | 1.0 | | |

*Typical Characteristics are at 25°C.

| Symbol | Parameter | Typical @ 25, $V_{CC} = 5.0$ V | | Unit |
|----------------------|---|--------------------------------|-----|------|
| | | Min | Max | |
| C_{IN} | Maximum Input Capacitance, Select Input | | 8.0 | pF |
| C_{NO} or C_{NC} | Analog I/O (switch off) | | 10 | |
| C_{COM} | Common I/O (switch off) | | 10 | |
| $C_{(ON)}$ | Feedthrough (switch on) | | 20 | |

ADDITIONAL APPLICATION CHARACTERISTICS (Voltages Referenced to GND Unless Noted)

| Symbol | Parameter | Condition | V_{CC} (V) | Typical | Unit |
|-----------|--|--|-----------------|---------|------|
| | | | | 25°C | |
| BW | Maximum On-Channel -3.0 dB Bandwidth or Minimum Frequency Response (Figure 10) | $V_{IN} = 0$ dBm V_{IN} centered between V_{CC} and GND (Figure 6) | 3.0 | 145 | MHz |
| | | | 4.5 | 170 | |
| | | | 5.5 | 175 | |
| V_{ONL} | Maximum Feedthrough On Loss | $V_{IN} = 0$ dBm @ 100 kHz to 50 MHz V_{IN} centered between V_{CC} and GND (Figure 6) | 3.0 | -2.0 | dB |
| | | | 4.5 | -2.0 | |
| | | | 5.5 | -2.0 | |
| V_{ISO} | Off-Channel Isolation (Figure 9) | $f = 100$ kHz; $V_{IS} = 1.0$ V RMS V_{IN} centered between V_{CC} and GND (Figure 6) | 3.0 | -93 | dB |
| | | | 4.5 | -93 | |
| | | | 5.5 | -93 | |
| Q | Charge Injection Select Input to Common I/O (Figure 14) | $V_{IN} = V_{CC}$ to GND, $F_{IS} = 20$ kHz $t_r = t_f = 3.0$ ns $R_{IS} = 0 \Omega$, $C_L = 1000$ pF $Q = C_L * \Delta V_{OUT}$ (Figure 7) | 3.0 | 1.5 | pC |
| | | | 5.5 | 3.0 | |
| THD | Total Harmonic Distortion THD + Noise (Figure 13) | $F_{IS} = 20$ Hz to 100 kHz, $R_L = R_{gen} = 600 \Omega$, $C_L = 50$ pF $V_{IS} = 5.0$ V _{PP} sine wave | 5.5 | 0.1 | % |
| VCT | Channel-to-Channel Crosstalk | $f = 100$ kHz; $V_{IS} = 1.0$ V RMS V_{IN} centered between V_{CC} and GND (Figure 6) | 5.5 | -90 | dB |
| | | | 3.0 | -90 | |





Figure 3. t_{BMM} (Time Break-Before-Make)





Figure 4. t_{ON}/t_{OFF}






Figure 5. t_{ON}/t_{OFF}

NLAS325



Channel switch control/s test socket is normalized. Off isolation is measured across an off channel. On loss is the bandwidth of an On switch. V_{ISO} , Bandwidth and V_{ONL} are independent of the input signal direction.

$$V_{ISO} = \text{Off Channel Isolation} = 20 \text{ Log} \left(\frac{V_{OUT}}{V_{IN}} \right) \text{ or } V_{IN} \text{ at } 100 \text{ kHz}$$

$$V_{ONL} = \text{On Channel Loss} = 20 \text{ Log} \left(\frac{V_{OUT}}{V_{IN}} \right) \text{ for } V_{IN} \text{ at } 100 \text{ kHz to } 50 \text{ MHz}$$

Bandwidth (BW) = the frequency 3.0 dB below V_{ONL}

V_{CT} = Use V_{ISO} setup and test to all other switch analog input/outputs terminated with 50 Ω

Figure 6. Off Channel Isolation/On Channel Loss (BW)/Crosstalk (On Channel to Off Channel)/ V_{ONL}




Figure 7. Charge Injection: (Q)




Figure 8. Switch Leakage vs. Temperature




Figure 9. Off-Channel Isolation




Figure 10. Typical Bandwidth and Phase Shift




Figure 11. t_{ON} and t_{OFF} vs. V_{CC} at 25°C




Figure 12. t_{ON} and t_{OFF} vs. Temp




Figure 13. Total Harmonic Distortion Plus Noise vs. Frequency




Figure 14. Charge Injection vs. COM Voltage

NLAS325




Figure 15. I_{CC} vs. Temp, $V_{CC} = 3.0$ V and 5.0 V




Figure 16. R_{ON} vs. V_{CC} , Temp = 25°C




Figure 17. R_{ON} vs Temp, $V_{CC} = 2.0$ V




Figure 18. R_{ON} vs. Temp, $V_{CC} = 2.5$ V




Figure 19. R_{ON} vs. Temp, $V_{CC} = 3.0$ V




Figure 20. R_{ON} vs. Temp, $V_{CC} = 4.5$ V

NLAS325




Figure 21. R_{ON} vs. Temp, V_{CC} = 5.0 V




Figure 22. R_{ON} vs. Temp, V_{CC} = 5.5 V

ORDERING INFORMATION

| Device Order Number | Package Type | Tape and Reel Shippingize† |
|---------------------|------------------|----------------------------|
| NLAS325USG | US8 (Pb-Free) | 3000 / Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.


MECHANICAL CASE OUTLINE PACKAGE DIMENSIONS



SCALE 4:1

US8
CASE 493
ISSUE F


DATE 01 SEP 2021



NOTES:


1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSION A DOES NOT INCLUDE MOLD FLASH, PROTRUSION, OR GATE BURR. MOLD FLASH, PROTRUSION, OR GATE BURR SHALL NOT EXCEED 0.14 (0.0055") PER SIDE.
4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH AND PROTRUSION SHALL NOT EXCEED 0.14 (0.0055") PER SIDE.
5. LEAD FINISH IS SOLDER PLATING WITH THICKNESS OF 0.0076-0.0203 MM (0.003-0.008").
6. ALL TOLERANCE UNLESS OTHERWISE SPECIFIED ±0.0508 MM (0.002").

| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|------|-----------|-------|
| | MIN. | MAX. | MIN. | MAX. |
| A | 1.90 | 2.10 | 0.075 | 0.083 |
| B | 2.20 | 2.40 | 0.087 | 0.094 |
| C | 0.60 | 0.90 | 0.024 | 0.035 |
| D | 0.17 | 0.25 | 0.007 | 0.010 |
| F | 0.20 | 0.35 | 0.008 | 0.014 |
| G | 0.50 BSC | | 0.020 BSC | |
| H | 0.40 REF | | 0.016 REF | |
| J | 0.10 | 0.18 | 0.004 | 0.007 |
| K | 0.00 | 0.10 | 0.000 | 0.004 |
| L | 3.00 | 3.25 | 0.118 | 0.128 |
| M | 0° | 6° | 0° | 6° |
| N | 0° | 10° | 0° | 10° |
| P | 0.23 | 0.34 | 0.010 | 0.013 |
| R | 0.23 | 0.33 | 0.009 | 0.013 |
| S | 0.37 | 0.47 | 0.015 | 0.019 |
| U | 0.60 | 0.80 | 0.024 | 0.031 |
| V | 0.12 BSC | | 0.005 BSC | |



* For additional information on our Pb-Free strategy and soldering details, please download the DN Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERM/D.

GENERIC MARKING DIAGRAM*



- XX = Specific Device Code
- M = Date Code
- = Pb-Free Package

(Note: Microdot may be in either location)

*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

| | | |
|-------------------------|--------------------|--|
| DOCUMENT NUMBER: | 98AON04475D | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION: | US8 | PAGE 1 OF 1 |

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

onsemi, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:

Technical Library: www.onsemi.com/design/resources/technical-documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support

For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales