



Technical Data:

Number of positions	17
Number of contacts	17
Contact Ø [mm]	1
Nominal current [A]	9 (for 0.50 mm ²) 4.5 (for 0.25 mm ²) 3 (for 0.14 mm ²)

Nominal voltage [V~]	160
Degree of pollution 3	
Test voltage [V~]	1500
Max. contact resistance [mΩ]	3
Insulation resistance [MΩ]	>10 ¹⁰
Protection	IP67 (connected)
Temperature range (fixed)	-40°C to 90°C
Temperature range (flex)	-25°C to 80°C

Further details see Product Specification 1204900050
The cordsets delivered packed into carton without PE-bag

TABLE 1

MOLEX PN	L [mm]	Tol. [mm]
1204900501	1000	+40
1204900502	2000	+60
1204900503	3000	+60
1204900504	4000	+60
1204900505	5000	+60
1204900506	10000	+80
1204900507	15000	+140
1204900508	20000	+140

TABLE 2

ITEM	QTY	DESCRIPTION
1	1	PLG M23 17P SC MA STR SHLD
2	1	PLG M23QC 17P FE STR SHLD
3	-	CABLE 3X(2X0.14)+2X0.50+4X0.14+4X0.25 WS

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

SYMBOLS	DIMENSION UNITS	SCALE	CURRENT REV DESC:					
▽ = 0	mm	1:1	EC NO: 625960					
▽ = 1	GENERAL TOLERANCES (UNLESS SPECIFIED)		DRWN: THAERDT	2019/10/21	CSE M23QC 17P SC MA STR WSOR FE 1XM SHLD			
▽ = 0	ANGULAR TOL ± 1.0°		CHK'D: RSILLER	2019/11/21				
▽ = 0	4 PLACES ±		APPR: RSILLER	2019/11/21				
▽ = 0	3 PLACES ±		INITIAL REVISION:					
▽ = 0	2 PLACES ± 0.05		DRWN: MSCHERER	2018/06/29	DOCUMENT NUMBER	DOC TYPE	DOC PART	REVISION
▽ = 0	1 PLACE ± 0.3		APPR: RSILLER	2019/11/21	1204901575	PSD	000	A
▽ = 0	0 PLACES ± 0.5		THIRD ANGLE PROJECTION			MATERIAL NUMBER	CUSTOMER	SHEET NUMBER
▽ = 0	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		DRAWING	SERIES	SEE TABLE 1	GENERAL MARKET		1 OF 1