

Linear Position Sensor in Hall Effect Technology (0 mm to 10 mm max.)


FEATURES

- Accurate linearity down to: $\pm 1\%$
- Electrical strokes from 0 mm to 10 mm
- Long life: Greater than 10M cycles
- Non contacting technology: Hall effect
- Model dedicated to all applications in harsh environments
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912


RoHS
COMPLIANT

QUICK REFERENCE DATA

| | |
|------------------|------------------------------------|
| Sensor type | LINEAR, non contacting hall effect |
| Output type | Wires |
| Market appliance | Industrial |
| Dimensions | 46 mm x 20.8 mm x 37 mm |

ELECTRICAL SPECIFICATIONS

| PARAMETER | STANDARD |
|-----------------------------|--|
| Electrical stroke | Up to 10 mm |
| Linearity | $\pm 2\%$ or $\pm 1\%$ |
| Supply voltage | $5 V_{DC} \pm 10\%$ |
| Supply current | < 16 mA typical |
| Output signal | Analog ratiometric 10 % to 90 % of V_{supply} or PWM 10 % to 90 % duty cycle |
| Over voltage protection | +20 V_{DC} |
| Reverse voltage protection | -10 V_{DC} |
| Load resistance recommended | Min. 1 k Ω for analog output and PWM output |
| Hysteresis | Static: 0.1 % of V_{supply} /Dynamic: 0.25 % of V_{supply} |
| Resolution | 12 bits |

MECHANICAL SPECIFICATIONS



| PARAMETER | |
|-------------------|---|
| Mechanical travel | 12 mm max. |
| Bearing type | Sleeve bearing |
| Standard | For spring loaded model: IP 51/without spring: Other on request |
| Weight | 26 g \pm 4 g |

ORDERING INFORMATION/DESCRIPTION

| 20 LHE | 1 | A | W | A | 1P30 | xxxx | e1 |
|--|---------------------------------------|------------------------------|-----------------------|--|--|-----------------|-------------|
| MODEL | FEATURES | LINEARITY | OUTPUT TYPE | OUTPUT SIGNAL | SHAFT TYPE | SPECIAL REQUEST | LEAD FINISH |
| | 1: Spring return 2: Without spring | X: $\pm 2\%$ A: $\pm 1\%$ | W: Wires Z: Custom | A: Analog increasing B: Analog decreasing C: PWM increasing D: PWM decreasing | 1: 3.175 mm 9: Special P: Plain T: Threaded M3 x 6 Z: Other type | | |
| Shaft length from mounting face 30 mm when full extended | | | | | | | |

SAP PART NUMBERING GUIDELINES

| 20 LHE | 2 | X | Z | C | 1T35 | xxxx |
|--------|------------------------------|-----------|-------------|----------------|------------|-----------------|
| MODEL | FEATURES | LINEARITY | OUTPUT TYPE | OUTPUT SIGNAL | SHAFT TYPE | SPECIAL REQUEST |
| | Without spring return system | $\pm 2\%$ | "Custom" | PWM increasing | | |



V_{OUT} ANALOG

V_{OUT} PWM

ENVIRONMENTAL SPECIFICATIONS

| | |
|---|--|
| Vibrations | 20 g from 10 Hz to 2000 Hz |
| Shocks | 3 shocks/axis; 50 g half a sine 11 ms |
| Operating temperature range | -40 °C; +85 °C |
| Life | > 10M of cycles |
| Speed (max.) | 60 mm/s |
| Immunity to radiated electromagnetic disturbances | 200 V/m 150 kHz/1 GHz IEC 62132-2 part 2 (level A) |
| Immunity to power frequency magnetic field | 200 A/m 50 Hz/60 Hz EN 61000-4-8 |
| Radiated electromagnetic emissions | 30 MHz/1 GHz < 30 dB μ V/m EN 61000-6-4 |
| Electrostatic discharges | Contact discharges: \pm 4 kV Air discharges: \pm 8 kV EN 61000-4-2 |
| Immunity to radiated RF field | 10 V/m 80 MHz to 1 GHz EN6100-4-3 |

| ENVIRONMENTAL SPECIFICATIONS | |
|------------------------------|--|
| Materials | |
| Housing | Thermoplastic housing |
| Mounting type | Flange with 2 holes \varnothing 4.5 mm |
| Shaft | \varnothing 3.175 mm (stainless steel) |
| Output | 3 lead wires (AWG 20) Length: 300 mm |
| Centering diameter | \varnothing 12 mm |
| Spring force | From 1.5 N to 7 N along stroke (typical) |

Note

- Nothing stated herein shall be construed as a guarantee of quality or durability.

DIMENSIONS in millimeters


| | |
|--------|---------------------|
| Wire | |
| YELLOW | GND (-) |
| RED | SIGNAL |
| GREEN | V _{cc} (+) |



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.