

Specification Sheet

Part Number: 553-50225

Slide Slit and optional center slits for easy wire insertion.
Smooth surface for clean and legible printing.

Supplied on a ladder style carrier so that markers can be kitted after printing.

A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.



ShrinkTrak Labels, 1-Sided, Unslit, Halogen Free, 1.5" (38.1mm), PO-X, Yellow, 150/box

| | |
|----------------|-------------|
| Article Number | 553-50225 |
| Type | HFST39-13YE |
| Color | Yellow (YE) |
| Quantity Per | box |

Product Description

HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.

Short Description

ShrinkTrak Labels, 1-Sided, Unslit, Halogen Free, 1.5" (38.1mm), PO-X, Yellow, 150/box

Global Part Name HFST39-13YE-PO-X-YE

Variant Thin-Wall

Width W (Imperial) 1.9

Width W (Metric) 48.26

Thickness T (Imperial) .003

Thickness T (Metric) .0762

Height H (Imperial) 2.26

Height H (Metric) 57.4

Width of Liner (Metric) 76.2

Width of Liner (Imperial) 3.0

Outside Diameter OD (Imperial) 1.5

Outside Diameter OD (Metric) 38.1

Outside Diameter Max (Imperial) 1.5

Outside Diameter Max (Metric) 38.1

Wall Thickness WT (Imperial) 0.04

Wall Thickness WT (Metric) 1.01

| | |
|------------------------------|---|
| Material | Polyolefin, cross-linked (PO-X) |
| Material Shortcut | PO-X |
| US MIL SPEC | SAE-AMS-DTL-23053/5 Class 1 and 3 SAE-AS81531 MIL-STD-202G Method 215K |
| Flammability | UL 224 VW-1 |
| Halogen Free | Yes |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -67°F to +275°F (-55°C to +135°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Certification/Specification | SAE - AMS - DTL-23053/5 Class 1 and 3 UL 224 125 °C 600V VW-1 SAE - AS81531 |
| Package Quantity (Imperial) | 150 |
| Package Quantity (Metric) | 150 |
| Customs Number | 3917320000 |
| Labels per Column | 1 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).