


JKL PART NUMBER	LENGTH A +/- 2mm	COLOR 5600° KELVIN	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF4183-20B	183mm	RGB HIGH OUTPUT WHITE	900 @ 0°C	380	5 ± 1	16,500±10%	25,000

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

PARTS ARE RoHS COMPLIANT.

METRIC  THIRD ANGLE PROJECTION	DIMENSIONS ARE IN MILLIMETERS	JKL COMPONENTS CORPORATION TITLE SINGLE LEAD TIPLESS MINIATURE FLUORESCENT LAMP					
	TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0					SIZE A	FSCM NO. 55335
DRAWN BY L. WENGSTROM	APPV'D BY L. R.	DATE 10/30/07	SCALE NONE	RELEASED DATE 10/30/07	REVISION DATE	REV. NO.	SHEET 1 OF 1

REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE
RELEASED		10/30/07
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		