



Y(B)1503 Directional Yagi Antenna

GOLD ANODIZED YAGI ANTENNA INSURES LONG-TERM PERFORMANCE


Laird's premium series Directional Yagi antennas are fully gold anodized for corrosion resistance. Our engineering staff has also optimized the product family for forward gain by computer analysis and then field-tested each for conformance.

FEATURES

- Every Yagi is tuned on a network analyzer for best power match and lowest VSWR.
- All Yagi antennas ship complete with a high quality cast aluminum mounting kit that includes stainless steel hardware and allows vertical or horizontal orientation during installation. (VHF models require light assembly)
- Available in gold or black (B) anodized finish

MARKETS

- Point to point directional and multiple point to omnidirectional outdoor antennas applications used by private organizations and government agencies around the globe.
- Typical applications include transportation such as railroad switching, remote locations reporting examples that include oil fields and weather conditions and meter data transmissions for utilities.




**Heavy-Duty Mounting
Kit Included**


MECHANICAL SPECIFICATIONS	
Material	Aluminum
Length	41-1/2"
Height	39-1/4"
Boom Diameter	7/8"
Weight	4 lbs
Rated Wind Velocity	150 mph (241 kph)
Rated Wind Velocity (with 0.5" radial ice)	80 mph (130 kph)
Equivalent Flat Area	0.504 sq. ft.
Cable	None
Termination	N-Female connector
Color	Gold or Black Anodized
Lightning Protection	Lightning Arrestor LABH350NN (Sold Separately)
Mounting Included	Heavy duty cast aluminum bracket accomodates up to 7/8" mast

ELECTRICAL SPECIFICATIONS

Frequency Range	150 - 174 MHz
Frequency Bandwidth	3 MHz typical
VSWR	< 2:1
Return Loss	-10dB max
Nominal Gain	7.1 dBd
Front to Back Ratio	17 dB
Maximum Power	300 W
Nominal Impedance	Ω 50
Polarization	Vertical or Horizontal
Pattern	Directional
Horizontal Beamwidth (For Horizontal Polarization)	78°
Vertical Beamwidth (For Vertical Polarization)	74°
Tuning	See cutting chart
Transmitting/Receiving	Both



Vertical-to-Vertical Polarization
Azimuthal Pattern (Y, Z, or E-plane)



Horizontal-to-Horizontal Polarization
Azimuthal Pattern (Y, Z, or H-plane)

TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE, and TE connectivity (logo) are trademarks owned or licensed by the TE Connectivity Ltd. family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE Connectivity warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE Connectivity will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE Connectivity product is installed. Useful lifetime of the original end product may vary but is not warranted to exceed one (1) year from the original date of the end product purchase.

©2022 TE Connectivity. All Rights Reserved.

08/22 Original