

FIC-M8M4

► FIELD WIREABLE CONNECTORS



Field Wireable Male M8 Pico
4 Pin, Non-Shielded, IP67
Plastic, Straight Connector
Field Adapter
Part Number: 58906

SPECIFICATIONS

Number of Contacts	4
Number of Connectors	1
Connector Body Material/Color	Plastic
Trunk Length (m)	No Trunk
Max Cable Diameter	5
Min Cable Diameter	4
Shield/No Shield	No Shield
Coupling Material/Color	Zinc Aluminum Nickel
Maximum Temp. (°C)	70
Current Rating (A)	4.0
Minimum Temp. (°C)	-25
Voltage Rating (V)	60 V ac/dc

By accepting cookies, we give you the best experience throughout our site, including access to My Account, My Library, and My Wish List. To learn more, visit our [privacy policy](#).



Chat with an Expert

IP Rating	IP67
Primary Connector Type	PICO
Primary Coupling Method	M8 Thread
Primary Gender	Male
Primary Orientation	Straight
Primary Number of Conductors	4
Secondary Connector Type	Flying Leads
Feature: Hazardous Area	No
Oil/Grease Resistant	No



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America

By accepting cookies, we give you the best experience throughout our site, including access to My Account, My Library, and My Wish List. To learn more, visit our [privacy policy](#).



Chat with an Expert