



SITOP SELECT/DIAGNOSIS MODULE/4X2-10A

SITOP select Diagnostics module 4-channel input: 24 V DC/40 A output: 24 V DC/4x 10 A threshold adjustable 2-10 A \*Ex approval no longer available\*

Input	
type of the power supply network	Controlled DC voltage (SITOP select is not designed for operation with DC UPS module 40 A (6EP1 931-2FC21/-2FC42))
supply voltage at DC rated value	24 V
input voltage at DC	22 ... 30 V
overvoltage overload capability	35 V; 100 ms
input current at rated input voltage 24 V rated value	40 A
Output	
voltage curve at output	controlled DC voltage
formula for output voltage	$V_{in} - \text{approx. } 0.3 \text{ V}$
relative overall tolerance of the voltage note	In accordance with the supplying input voltage
number of outputs	4
output current up to 60 °C per output rated value	10 A
adjustable current response value current of the current-dependent overload release	2 ... 10 A
type of response value setting	via potentiometer
product feature parallel switching of outputs	No
type of outputs connection	Simultaneous connection of all outputs after power up of the supply voltage, delay time of 24 ms or 100 ms programmable for sequential connection
Efficiency	
efficiency in percent	97 %
power loss [W] at rated output voltage for rated value of the output current typical	30 W
Switch-off characteristic per output	
switching characteristic	
<ul style="list-style-type: none"> <li>of the excess current</li> <li>of the current limitation</li> <li>of the immediate switch-off</li> </ul>	$I_{out} = 1.0 \dots 1.3 \times \text{set value}$ , switch-off after approx. 5 s $I_{out} = 1.3 \times \text{set value}$ , switch-off after approx. 50 ... 100 ms $I_{out} > \text{set value and } V_{in} < 20 \text{ V}$ , switch-off after approx. 0.5 ms
residual current at switch-off typical	20 mA
design of the reset device/resetting mechanism	Using keys on the module
remote reset function	-
Protection and monitoring	
fuse protection type at input	Blade-type fuse per output (equipped when delivered with 15 A fuse)
display version for normal operation	Two-color LED per output: green LED for "Output switched through"; red LED for "Output switched off due to overcurrent"
design of the switching contact for signaling function	Common signal contact (NO contact, rating 0.5 A/24 V DC)
Safety	
galvanic isolation between input and output at switch-off	No
standard for safety	according to EN 60950-1 and EN 50178

operating resource protection class	Class III
protection class IP	IP20
<b>Approvals</b>	
certificate of suitability	Yes
<ul style="list-style-type: none"> <li>• CE marking</li> <li>• UL approval</li> </ul>	Yes; UL-Recognized (UL 2367) File E328600; cULus-Listed (UL 508, CSA C22.2 No. 107.1) File E197259
<ul style="list-style-type: none"> <li>• ATEX</li> </ul>	No
certificate of suitability	No
<ul style="list-style-type: none"> <li>• IECEx</li> </ul>	No
certificate of suitability	Yes
<ul style="list-style-type: none"> <li>• EAC approval</li> <li>• shipbuilding approval</li> </ul>	No
<b>EMC</b>	
standard	
<ul style="list-style-type: none"> <li>• for emitted interference</li> <li>• for interference immunity</li> </ul>	EN 55022 Class B EN 61000-6-2
<b>environmental conditions</b>	
ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> <li>• during transport</li> <li>• during storage</li> </ul>	0 ... 60 °C; with natural convection -40 ... +85 °C -40 ... +85 °C
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
<b>Mechanics</b>	
type of electrical connection	screw-type terminals
<ul style="list-style-type: none"> <li>• at input</li> <li>• at output</li> <li>• for signaling contact</li> <li>• for auxiliary contacts</li> </ul>	+24 V: 2 screw terminals for 0.5 ... 16 mm <sup>2</sup> ; 0 V: 2 screw terminals for 0.5 ... 4 mm <sup>2</sup> Output 1 ... 4: 1 screw terminal each for 0.22 ... 4 mm <sup>2</sup> 2 screw terminals for 0.22 ... 4 mm <sup>2</sup> -
width of the enclosure	72 mm
height of the enclosure	90 mm
depth of the enclosure	90 mm
installation width	72 mm
mounting height	190 mm
required spacing	
<ul style="list-style-type: none"> <li>• top</li> <li>• bottom</li> <li>• left</li> <li>• right</li> </ul>	50 mm 50 mm 0 mm 0 mm
net weight	0.4 kg
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
product component included	4x blade-type fuse 15 A
MTBF at 40 °C	616 675 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

