

Connector assembly frame - HC-CIF-2B6-BFFD-FH-AL - 1404214

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



HEAVYCON plug assembly frame, lower part for double locking latch, for housing with double locking latch or HC-CIF..HFFD..., for two type B6 contact inserts

Product Features

- Sturdy metal version
- Open base, pre-assembled cable harnesses can be used
- Standardized design; both PE sheets for inserts are connected conductively
- Safe capacitive PE even when connected slightly askew



Key commercial data

Packing unit	1 1
Custom tariff number	85389099
Country of origin	Poland

Technical data

Dimensions

Length	120 mm
--------	--------

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

General

Design	For 2xB6
Material	Cast aluminum, uncoated

Classifications

eCl@ss

eCl@ss 4.0	27140816
------------	----------

Connector assembly frame - HC-CIF-2B6-BFFD-FH-AL - 1404214

Classifications

eCl@ss

eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440209

ETIM


ETIM 3.0	EC002310
ETIM 4.0	EC002310
ETIM 5.0	EC002310

UNSPSC

UNSPSC 6.01	43172601
UNSPSC 7.0901	39121416
UNSPSC 11	43172601
UNSPSC 12.01	39121408
UNSPSC 13.2	39121408


Drawings

Dimensioned drawing



Dimensional drawing top view

Dimensioned drawing



Dimensional drawing, a = 120 mm