



Jun. 2021 Ver.2.0  
TDK Corporation

## Multilayer Diplexer


For LTE

DPX Series 2.0x1.25mm [EIA 0805] TYPE

P/N: **DPX201880DT-4061A2**

## DPX201880DT-4061A2

### SHAPES AND DIMENSIONS



Dimensions (mm)

L	W	T	a	b	c	d	e
2.00	1.25	0.90	0.65	0.35	0.30	0.20	0.20
+/-0.15	+/-0.15	+/-0.10	+/-0.15	+/-0.15	+/-0.15	+/-0.15	+/-0.15

Terminal functions

(1)	GND
(2)	Common Port
(3)	GND

(4)	High-Band Port
(5)	GND
(6)	Low-Band Port

### TERMINATION FINISH

Material
Sn plate

**DPX201880DT-4061A2****ELECTRICAL CHARACTERISTICS**

( Measurement )

**Low-Band**

Parameter	Frequency (MHz)	TDK Spec		
		Min.	Typ.	Max.
Insertion Loss (dB)	698 to 960	-	0.63	0.85
	960 to 1447	-	0.71	0.85
	1447 to 1511	-	0.98	1.60
VSWR (Low-Band Port)	698 to 960	-	1.12	1.92
	960 to 1447	-	1.21	1.92
	1447 to 1511	-	1.21	1.92
Attenuation (dB)	1710 to 1880	10	15.0	-
	1880 to 2170	10	15.0	-
	2170 to 2700	10	15.0	-
Characteristic Impedance (ohm)		50 (Nominal)		

Ta = +25+/-5°C

**High-Band**

Parameter	Frequency (MHz)	TDK Spec		
		Min.	Typ.	Max.
Insertion Loss (dB)	1710 to 1880	-	1.02	1.60
	1880 to 2170	-	0.29	1.00
	2170 to 2700	-	0.52	1.00
VSWR (High-Band Port)	1710 to 1880	-	1.35	1.92
	1880 to 2170	-	1.40	1.92
	2170 to 2700	-	1.86	2.32
Attenuation (dB)	698 to 960	7	9.0	-
	960 to 1447	7	9.0	-
	1447 to 1511	10	15.0	-
Characteristic Impedance (ohm)		50 (Nominal)		

Ta = +25+/-5°C

## DPX201880DT-4061A2

### ■ MAXIMUM RATINGS









( Measurement )

Parameter		TDK Spec	Conditions
Operating temperature (°C)		-40 to +85 °C	
Storage temperature (°C)		-40 to +85 °C	
Power Handling (W) *1	Frequency (MHz)		
Low-Band	698 to 1511	1	CW
High-Band	1710 to 2700	1	CW
Human Body Model : HBM	@Each Port (V)	+/-1000	100pF / 1500ohm
Machine Model : MM	@Each Port (V)	+/-150	200pF / 0ohm
Charged Device Model : CDM	@Each Port (V)	+/-500	Humidity : 60%RH max

\*1 : Refer to 3GPP TS 38.101-1 V15.2.0


# DPX201880DT-4061A2

## FREQUENCY CHARACTERISTICS




## DPX201880DT-4061A2

### RECOMMENDED LAND PATTERN



### EVALUATION BOARD



\* Line width should be designed to match 50 ohm characteristic impedance depending on PCB material and thickness.


\*\* The position of the thru hole which have possibility of influence to the performance are indicated by dimension line.

### ENVIRONMENT INFORMATION

RoHS Statement  
RoHS Compliance

## DPX201880DT-4061A2

### RECOMMENDED REFLOW PROFILE



Preheating			Soldering			
			Critical zone (T3 to T4)		Peak	
Temp.		Time	Temp.	Time	Temp.	Time
T1	T2	t1	T3	t2	T4	t3 *
150°C	200°C	60 to 120sec	217°C	60 to 120sec	240 to 260°C	30 sec Max


\* t3 : Time within 5°C of actual peak temperature

The maximum number of reflow is 3.


Note: Lead free solder is recommended.  
Recommended solder is Sn-3.0Ag-0.5Cu. (M705 by Senju Metal Industry)

**DPX201880DT-4061A2****PACKAGING STYLE**

## Reel Dimensions



Dimensions in mm



## Dimensions (mm)

A	B	C	D	E	F	G	H	J	K	t
1.45	2.2	8.0	3.5	1.75	4.0	2.0	4.0	1.5	1.15	0.25
$\pm 0.05$	$\pm 0.05$	$+0.3/-0.1$	$\pm 0.05$	$\pm 0.1$	$\pm 0.1$	$\pm 0.05$	$\pm 0.1$	$+0.1/-0$	MAX	$\pm 0.05$

**STANDARD PACKAGE QUANTITY****( pieces/reel )**

2,000

All specifications are subject to change without notice.

TDK Technology - Proprietary and Confidential Information of TDK Group Companies



## REMINDERS FOR USING THESE PRODUCTS

Before using these products, be sure to request the delivery specifications.

### SAFETY REMINDERS

Please pay sufficient attention to the warnings for safe designing when using these products.

 <b>REMINDERS</b>
--

The products listed on this specification sheet are intended for use in general electronic equipment (AV equipment, telecommunications equipment, home appliances, amusement equipment, computer equipment, personal equipment, office equipment, measurement equipment, industrial robots) under a normal operation and use condition.

The products are not designed or warranted to meet the requirements of the applications listed below, whose performance and/or quality require a more stringent level of safety or reliability, or whose failure, malfunction or trouble could cause serious damage to society, person or property. Please understand that we are not responsible for any damage or liability caused by use of the products in any of the applications below or for any other use exceeding the range or conditions set forth in this specification sheet.

1. Aerospace/Aviation equipment
2. Transportation equipment (cars, electric trains, ships, etc.)
3. Medical equipment
4. Power-generation control equipment
5. Atomic energy-related equipment
6. Seabed equipment
7. Transportation control equipment
8. Public information-processing equipment
9. Military equipment
10. Electric heating apparatus, burning equipment
11. Disaster prevention/crime prevention equipment
12. Safety equipment
13. Other applications that are not considered general-purpose applications

When using this product in general-purpose applications, you are kindly requested to take into consideration securing protection circuit/equipment or providing backup circuits, etc., to ensure higher safety.