


			1		
	Part Number:		DRAWN		
	TE102603-1		CJ	12/9/2016	
		2003-1	CHECKED	12/9/2016	
			P.D.		
	Description:	nical Transducer	APPROVED	12/0/2016	
	Electro-Mecha	illicai Transuucei	J.S.	12/9/2016	


This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at www.dbunlimitedco.com

Top View




Weight

Side View



Bottom View



4) Subject to change or redrawn without notice

Items	Specifications	Conditions					
Sound Pressure Level	88	dB (@ 10cm)					
Resonant Frequency	2,670	Hz					
Rated Voltage	3.6	V		REVISION HISTO	RY		
Voltage Range	2.5 ~ 4.5	V	REV	DESCRIPTION	DATE	APPROVED	
Coil Resistance	16	Ω		Released from Engineering	10/21/2013	J.S.	
Max. Rated Current	100	mA	1	Updated to new template	12/9/2016	J.S.	
Storage Temperature	-40 ~ +85	°C	2	Updated storage temp, voltage range	5/20/2019	C.E.	
Operating Temperature	-30 ~ +70	°C	· ·	NOTES			
Connection Method	Surface Pads			1) All dimensions are in mm unless otherwise noted			
Mount Type	Surface Mount			2) All tolerances are ± 0.5 mm unless otherwise noted			
Housing Material	LCP		3) All parts meet RoHS				

Additional considerations can be found at www.dbunlimitedco.com/technical-articles.