

## ANNA-40-5-S

~15° spot beam with 5 optics

### SPECIFICATION:

Dimensions	Ø 40.0 mm
Height	10.7 mm
Fastening	glue, pin
ROHS compliant	yes ⓘ




### MATERIALS:

Component	Type	Material	Colour	Finish
ANNA-40-5-S	Multi-lens	PMMA	clear	

### ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C11713_ANNA-40-5-S » Box size: 480 x 280 x 300 mm	760	120	40	7.2



See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

### OPTICAL RESULTS (MEASURED):

#### CREE LED

LED	XP-E
FWHM / FWTM	12.0° / 24.0°
Efficiency	93 %
Peak intensity	12.7 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	

#### CREE LED

LED	XP-G
FWHM / FWTM	18.0° / 39.0°
Efficiency	93 %
Peak intensity	5.9 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	

#### LUMILEDS

LED	LUXEON A
FWHM / FWTM	19.0° / 40.0°
Efficiency	87 %
Peak intensity	5.7 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	

#### LUMILEDS

LED	LUXEON Rebel
FWHM / FWTM	13.0° / 28.0°
Efficiency	92 %
Peak intensity	9.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	

#### OPTICAL RESULTS (MEASURED):

##### LUMILEDS

LED LUXEON Rebel ES  
FWHM / FWTM 18.0° / 36.0°  
Efficiency 93 %  
Peak intensity 6.1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:

##### NICHIA

LED NCSxx19A  
FWHM / FWTM 16.0° / 35.0°  
Efficiency 91 %  
Peak intensity 6.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:


##### NICHIA

LED NVSxx19A  
FWHM / FWTM 19.0° / 42.0°  
Efficiency 91 %  
Peak intensity 4.9 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:

##### OSRAM

Opto Semiconductors

LED Duris S5 (2 chip)  
FWHM / FWTM 18.0° / 41.0°  
Efficiency 90 %  
Peak intensity 6 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



## OPTICAL RESULTS (MEASURED):

### OSRAM

Opto Semiconductors

LED OSLON SSL 150  
FWHM / FWTM 12.0° / 22.0°  
Efficiency 90 %  
Peak intensity 13.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:

### OSRAM

Opto Semiconductors

LED OSLON SSL 80  
FWHM / FWTM 11.0° / 26.0°  
Efficiency 93 %  
Peak intensity 11.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:

## OPTICAL RESULTS (SIMULATED):

### SHARP

LED	Double Dome (GM2BB)
FWHM / FWTM	12.0°
Efficiency	%
LEDs/each optic	1
Light colour	White
Required components:	

### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)