

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		TEST METHOD		REQUIREMENTS		QT	AT
RATING	OPERATING TEMPERATURE RANGE	-35°C TO 85°C (NOTE 1)	STORAGE TEMPERATURE RANGE			-10°C TO 60°C	
	VOLTAGE	30V AC/DC	APPLICABLE CONNECTOR			BM20*(0.8)-34DS-0.4V (**)	
	CURRENT	0.3A					
SPECIFICATIONS							
ITEM	TEST METHOD			REQUIREMENTS			
CONSTRUCTION			VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.				
MARKING	CONFIRMED VISUALLY.						
ELECTRIC CHARACTERISTICS							
CONTACT RESISTANCE	20mV AC OR LESS 1KHz, 1m A.		100mΩ MAX.		X		
INSULATION RESISTANCE	100V DC.		50MΩ MIN.		X		
VOLTAGE PROOF	100V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.		X		
MECHANICAL CHARACTERISTICS							
MECHANICAL OPERATION	10TIMES INSERTIONS AND EXTRACTIONS.		① CONTACT RESISTANCE: 100mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X		
VIBRATION	FREQUENCY 10 TO 55 TO 10 Hz, APPROX 5min, SINGLE AMPLITUDE 0.75 mm, 100CYCLES, FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X		
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X		
ENVIRONMENTAL CHARACTERISTICS							
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 → +85°C TIME 30 → 30 min UNDER 5 CYCLES. (RELOCATION TIME TO CHAMBER: WITHIN 2-3 min)		① CONTACT RESISTANCE: 100mΩ MAX. ② INSULATION RESISTANCE: 50MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X		
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.		① CONTACT RESISTANCE: 100mΩ MAX. ② INSULATION RESISTANCE: 25MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X		
SULPHUR DIOXIDE	EXPOSED IN 25 PPM FOR 96h, 25°C, 75%. (REFER TO JIS C 60068)		① CONTACT RESISTANCE: 100mΩ MAX. ② NO EVIDENCE OF CORROSION WHICH AFFECTS TO OPERATION OF CONNECTOR.		X		
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE			
REMARKS	NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT						
	UNLESS OTHERWISE SPECIFIED, REFER TO JIS C 5402 and IEC 60512.						
	Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-343535-01			
	APPROVED		KH. IKEDA	12.03.16			
CHECKED		AR. TAKAHASHI	12.03.16				
DESIGNED		YK. SATAKE	12.03.16				
DRAWN		KR. AJITO	12.03.15				
<div style="display: flex; justify-content: space-between;"> HIROSE ELECTRIC CO., LTD. CL684-9019-0-51 1/1 </div>							