

Outline Drawing

1	2	3	4	5	6
CUSTOMER P/N:				Rev.	NOTES
				V1.0	New Issue
				V1.1	Modify the width of FPC goldfinger
				V1.2	Update the drawing outline

Dimensions (mm): 63.90±0.20 (OUTLINE), 76.90±0.20 (OUTLINE), 72.88±0.20 (BZ A-A), 70.08 (LCD A-A), 3.42±0.20, 2.07, 2.01, 3.41±0.20, 15.60±0.30, 55.96±0.50, 1.30, 5.4, 27.50±0.10, 1.13±0.1, 0.13±0.03, 0.30±0.05, 3.10±0.15, 3.91±0.05, 0.80±0.05, 0.30±0.05, 0.30±0.05, 0.50±0.05, 0.50, 3.91±0.05, 0.80±0.05, 0.30±0.05, 0.30±0.05

PIN	PIN NAME	PIN	PIN NAME
1	VBL-	28	R0
2	VBL-	29	R1
3	VBL+	30	R2
4	VBL+	31	R3
5	YU	32	R4
6	XR	33	R5
7	NC	34	R6
8	/RESET	35	R7
9	SPENA(nCS)	36	HSYNC
10	SPCLK(SCL)	37	VSYNC
11	SPDAT(SDI)	38	clk(dotclk)
12	B0	39	NC
13	B1	40	NC
14	B2	41	VDDIO
15	B3	42	VCC
16	B4	43	YD
17	B5	44	XL
18	B6	45	NC
19	B7	46	NC
20	G0	47	NC
21	G1	48	NC
22	G2	49	NC
23	G3	50	NC
24	G4	51	NC
25	G5	52	ENB(DEN)
26	G6	53	GND
27	G7	54	AVSS

Notes:

- 1.DISPLAY TYPE: 3.5" TFT
- 2.DISPLAY MODE: Transmissive
- 3.VIEW DIRECTION: 12 o'clock
- 4.OPERATION TEMPERATURE: -20°C~+70°C
- 5.STORAGE TEMPERATURE: -30°C~+80°C
- 6.DRIVER IC: HX8238-D
- 7.REQUIREMENT ON ENVIRONMENT PROTECTION: ROHS

Electrical Symbol:
 A1 A2: Electrical Pin with LED+PS
 K2 K1: Electrical Pin with LED-PS
 VF=18.6±1.20V;IF=20mA

DLC Display Co., Ltd

Title	TFT LCM OUTLINE	Unit	mm
Part No.	DLC0350ABM06RT-2	Scale	1:1
Revision	V1.2	Page	1/1
Date	2018-09-21	3rd Angle	

Customer Approval	Drawn:		
	Checked:		
	Approved:		
	Critical Dim.		
	Reference Dim.	()	