

A2C 50/70 3FT-FE**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Power feed-in**

Our wide range of W-Series terminal blocks with our WPD main line branch terminals, which are optimised to guarantee both convenience and space gains, ensures a secure and convenient connection at the power feed-in.

General ordering data

| | |
|------------|---|
| Version | Feed-through terminal, PUSH IN, 50 mm ² , 1000 V, 150 A, dark beige, black, yellow |
| Order No. | 2663310000 |
| Type | A2C 50/70 3FT-FE |
| GTIN (EAN) | 4050118896022 |
| Qty. | 1 pc(s). |

Creation date August 25, 2021 7:50:48 PM CEST

Catalogue status 20.08.2021 / We reserve the right to make technical changes.

A2C 50/70 3FT-FE**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

| | | | |
|------------|----------|-----------------|------------|
| Depth | 80.5 mm | Depth (inches) | 3.169 inch |
| Height | 101.5 mm | Height (inches) | 3.996 inch |
| Width | 80 mm | Width (inches) | 3.15 inch |
| Net weight | 466 g | | |

Temperatures

| | | | |
|----------------------------------|----------------|----------------------------------|--------|
| Storage temperature | -25 °C...55 °C | Continuous operating temp., min. | -60 °C |
| Continuous operating temp., max. | 130 °C | | |

Material data

| | | | |
|--------------------------------|--------|---------------------------|---------------------------|
| Material | Wemid | Colour | dark beige, black, yellow |
| Colour of operational elements | orange | UL 94 flammability rating | V-0 |

System specifications

| | | | |
|-------------------------------|-------|-------------------------------------|----|
| End cover plate required | No | Number of potentials | 4 |
| Number of levels | 1 | Number of clamping points per level | 8 |
| Number of potentials per tier | 4 | Levels cross-connected internally | No |
| Rail | TS 35 | N-function | No |
| PE function | No | PEN function | No |

Additional technical data

| | | | |
|----------------|--------|------------------|-------|
| Open sides | closed | Snap-on | Yes |
| Type of fixing | TS 35 | Type of mounting | TS 35 |

Conductors for clamping (rated connection)

| | | | |
|---|--------------------|---|--------------------|
| Blade size | 1.0 x 5.5 mm | Clamping range, max. | 70 mm ² |
| Clamping range, min. | 10 mm ² | Connection cross-section, stranded, max. | 70 mm ² |
| Connection cross-section, stranded, min. | 10 mm ² | Connection direction | on side |
| Number of connections | 8 | Stripping length | 30 mm |
| Twin wire-end ferrules, max. | 10 mm ² | Twin wire-end ferrules, min. | 4 mm ² |
| Type of connection | PUSH IN | Wire connection cross section AWG, max. | AWG 2/0 |
| Wire connection cross section AWG, min. | AWG 8 | Wire connection cross section, finely stranded, max. | 70 mm ² |
| Wire connection cross section, finely stranded, min. | 10 mm ² | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max. | 50 mm ² |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min. | 10 mm ² | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max. | 50 mm ² |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min. | 10 mm ² | Wire connection cross-section, solid core, max. | 70 mm ² |
| Wire connection cross-section, solid core, min. | 10 mm ² | | |

A2C 50/70 3FT-FE**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**General**

| | | | |
|---|---------|---|---------------|
| Rail | TS 35 | Standards | IEC 60947-7-1 |
| Wire connection cross section AWG, max. | AWG 2/0 | Wire connection cross section AWG, min. | AWG 8 |

Rating data

| | | | |
|--|--------------------|---------------------------------|---------------|
| Rated cross-section | 50 mm ² | Rated voltage | 1,000 V |
| Rated DC voltage | 1,500 V DC | Rated current | 150 A |
| Current at maximum wires | 150 A | Standards | IEC 60947-7-1 |
| Volume resistance according to IEC 60947-7-x | 0.21 mΩ | Rated impulse withstand voltage | 8 kV |
| Pollution severity | 3 | Surge voltage category | III |

UL rating data

| | | | |
|--|--------|--|--------|
| Certificate No. (cURus) | E60693 | Conductor size Factory wiring max. (cURus) | 00 AWG |
| Conductor size Factory wiring min. (cURus) | 8 AWG | Conductor size Field wiring max. (cURus) | 00 AWG |
| Conductor size Field wiring min. (cURus) | 8 AWG | Current size B (cURus) | 175 A |
| Current size C (cURus) | 175 A | Current size D (cURus) | 5 A |
| Voltage size B (cURus) | 1000 V | Voltage size C (cURus) | 1000 V |
| Voltage size D (cURus) | 600 V | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC000897 | ETIM 7.0 | EC000897 |
| ETIM 8.0 | EC000897 | ECLASS 9.0 | 27-14-11-20 |
| ECLASS 9.1 | 27-14-11-20 | ECLASS 10.0 | 27-14-11-20 |
| ECLASS 11.0 | 27-14-11-20 | | |

Approvals

Approvals



UL File Number Search E60693

Downloads

| | |
|---|---|
| Approval/Certificate/Document of Conformity | Declaration of Conformity |
| Engineering Data | STEP |
| User Documentation | Instruction sheet |
| Catalogues | Catalogues in PDF-format |

Data sheet

A2C 50/70 3FT-FE

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

