HellermannTyton

Specification Sheet

Part Number: 596-00887

Made with UV-stable inks and materials for durability and weather resistance.

Reflective properties to meet applicable NEC code requirements for reflective identification.

Supplied with an aggressive adhesive to ensure long life.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

RAPID SHUTDOWN SWITCH FOR SOLAR PV SYSTEM

Solar Label, Reflective, Photovoltaic System...Shutdown, 6.5" x 1.0", VL, Red, 50/roll

| Article Number | 596-00887 |
|---------------------|--|
| Туре | PSEWRS17 |
| Color | Red (RD) |
| Quantity Per | roll |
| Product Description | HellermannTyton Pre-Printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code® (NEC®) and the International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder-coated surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed. |

| Short Description | Solar Label, Reflective, Photovoltaic SystemShutdown, 6.5" x 1.0", VL, Red, 50/roll |
|---------------------------|---|
| Global Part Name | PSEWRS17-505/281-RD |
| | |
| Width W (Imperial) | 6.5 |
| Width W (Metric) | 165.1 |
| Thickness T (Imperial) | 0.0025 |
| Thickness T (Metric) | 64.0 |
| Height H (Imperial) | 1.0 |
| Height H (Metric) | 25.40 |
| Width of Liner (Metric) | 28.57 |
| Width of Liner (Imperial) | 1.125 |
| | |
| | |
| Material | Type 505/281, UV-stabilised, reflective vinyl with clear polyester laminate (505/281) |
| Material Shortcut | 505/281 |
| Adhesive | Acrylic |
| Halogen Free | No |

| UV Resistant (Yes/No) | Yes |
|--------------------------------|-----------------------------------|
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Operating Temperature | -40°F to +174°F (-40°C to +79°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Certification/Specification | NEC2017 NEC2023 NEC2020 |
| Warranty (US) | Yes |
| UL Recognized (US) | Yes |
| | |
| Package Quantity (Imperial) | 50 |
| Package Quantity (Metric) | 50 |
| Customs Number | 3919102055 |
| Labels per Column | 1 |
| Labels per Row | 1 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global

customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (<u>www.hellermann.tyton.com</u>).

© 2023 HellermannTyton. All Rights Reserved. Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions