



- Material:**
- Cable: USB2.0 UL2725 [28AWG(7/0.12TC+AL):*1P+ 28AWG(7/0.12TC)*2C]+AEB(488 TC)
 - Jacket: Black
 - OD: 3.5MM
 - Connectors: Micro USB 5P A/M Solder Type
 - Shell: Nickel
 - Pin: G/F
 - Insulator Color: Black
 - Outer Jacket: Black PVC-50P
- Electrical:**
- 100% short, open, miswire test
 - Conduct resistance: 2Ω Max.
 - Insulation resistance: 5MΩ Min.
 - Hi-Pot test: 300V DC

| | | | | | | | | | |
|-----------|-------|--|--|--|--|----------|----------|----------|--|
| Scale | 1:1 | | | | | | | Name | Item No. AK67301-0.5-R |
| TOLERANCE | | | | | | Drawn | 10.19.11 | Chappell | |
| X.X | ±0.40 | | | | | Approved | | | |
| X.XX | ±0.25 | | | | | | | | Title USB2.0 Micro Connection Cable, 0.5 Meter USB A Micro Male <=> USB A Micro Male |
| X.XXX | ±0.15 | | | | | | | | Drawing No. |
| Angle | ±3° | | | | | | | | rev00 |
| | | | | | | | | | Replace |
| | | | | | | | | | Sheet |

