

Surface Mount NP General Purpose Transistor




2N2907AUB

Obsolete (2N2907AUBTX, 2N2907AUBTXV)

Features:

- Ceramic 3 pin surface mount package (UBN)
- Miniature package to minimize circuit board area
- Hermetically sealed
- Footprint and pin-out matches SOT-23 package transistors
- Processed per MIL-PRF-19500/291



Description:

The 2N2907AUB, (TX, TXV - **Obsolete**) are miniature, hermetically sealed, ceramic surface mount general purpose switching transistors. The miniature three pin ceramic package is ideal for upgrading commercial grade circuits to military reliability levels where plastic SOT-23 devices have been used. The "UB" suffix denotes the 3 terminal chip carrier package, type "B" per MIL-PRF-19500/291.


Typical screening and lot acceptance tests per MIL-PRF-19500/291.

The burn-in condition is $V_{CB} = 30\text{ V}$, $P_D = 200\text{ mW}$, $T_A = 25^\circ\text{ C}$, $t = 80\text{ hrs}$.

Refer to MIL-PRF-19500/291 for complete requirements. In addition, the TX and TXV versions receive 100 % thermal response testing.

Applications:

- General switching
- Amplification
- Signal processing
- Radio transmission
- Logic gates



General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology
 2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

Surface Mount PNP General Purpose Transistor



2N2907AUB

Obsolete (2N2907AUBTX, 2N2907AUBTXV)

Electrical Specifications

Absolute Maximum Ratings ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Collector-Base Voltage	60 V
Collector-Emitter Voltage	60 V
Emitter-Base Voltage	5.0 V
Collector Current-Continuous	600 mA
Operating Junction Temperature (T_J)	-65°C to $+200^\circ\text{C}$
Storage Junction Temperature (T_{stg})	-65°C to $+200^\circ\text{C}$
Power Dissipation @ $T_A = 25^\circ\text{C}$	0.5 W
Power Dissipation @ $T_c = 25^\circ\text{C}$	1.00 W ⁽¹⁾
Soldering Temperature (vapor phase reflow for 30 seconds)	215° C
Soldering Temperature (heated collet for 5 seconds)	260° C

Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

SYMBOL	PARAMETER	MIN	MAX	UNITS	TEST CONDITIONS
OFF CHARACTERISTICS					
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage	60	-	V	$I_C = 10\ \mu\text{A}$, $I_E = 0$
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage	60	-	V	$I_C = 10\ \text{mA}$, $I_B = 0$ ⁽²⁾
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage	5.0	-	V	$I_E = 10\ \mu\text{A}$, $I_C = 0$
I_{CBO}	Collector-Base Cutoff Current	-	10	μA	$V_{CB} = 50\ \text{V}$, $I_E = 0$
		-	10	μA	$V_{CB} = 50\ \text{V}$, $I_E = 0$, $T_A = 150^\circ\text{C}$
I_{EBO}	Emitter-Base Cutoff Current	-	10	μA	$V_{CE} = 4.0\ \text{V}$, $I_C = 0$
I_{CES}	Collector Emitter Cutoff Current	-	10	nA	$V_{EB} = 50\ \text{V}$
ON CHARACTERISTICS					
h_{FE}	Forward-Current Transfer Ratio	75	-	-	$V_{CE} = 10\ \text{V}$, $I_C = 0.1\ \text{mA}$
		100	450	-	$V_{CE} = 10\ \text{V}$, $I_C = 1.0\ \text{mA}$
		100	-	-	$V_{CE} = 10\ \text{V}$, $I_C = 10\ \text{mA}$
		100	300	-	$V_{CE} = 10\ \text{V}$, $I_C = 150\ \text{mA}$ ⁽²⁾
		50	-	-	$V_{CE} = 10\ \text{V}$, $I_C = 500\ \text{mA}$ ⁽²⁾
		50	-	-	$V_{CE} = 10\ \text{V}$, $I_C = 1.0\ \text{mA}$, $T_A = -55^\circ\text{C}$

Note:

- Derate linearly 6.6 mW/° C above 25° C
- Pulse Width $\leq 300\ \mu\text{s}$, Duty Cycle $\leq 2.0\ \%$

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

Surface Mount PNP General Purpose Transistor



2N2907AUB

Obsolete (2N2907AUBTX, 2N2907AUBTXV)

Electrical Specifications

Electrical Characteristics (T _A = 25° C unless otherwise noted)					
SYMBOL	PARAMETER	MIN	MAX	UNITS	TEST CONDITIONS
ON CHARACTERISTICS					
V _{CE(SAT)}	Collector-Emitter Saturation Voltage	-	0.40	V	I _C = 150 mA, I _B = 15 mA ⁽²⁾
		-	1.60	V	I _C = 500 mA, I _B = 50 mA ⁽²⁾
V _{BE(SAT)}	Base-Emitter Saturation Voltage	-	1.30	V	I _C = 150 mA, I _B = 15 mA ⁽²⁾
		-	2.60	V	I _C = 500 mA, I _B = 50 mA ⁽²⁾
SMALL-SIGNAL CHARACTERISTICS					
h _{fe}	Small Signal Forward Current Transfer Ratio	100	-	-	V _{CE} = 10 V, I _C = 1.0 mA, f = 1.0 kHz
h _{fe}	Small Signal Forward Current Transfer Ratio	2.0	-	-	V _{CE} = 20 V, I _C = 20 mA, f = 100 MHz
C _{obo}	Open Circuit Output Capacitance	-	8.0	pF	V _{CB} = 10 V, 100 kHz ≤ f ≤ 1.0 MHz
C _{ibo}	Input Capacitance (Output Open)	-	30	pF	V _{EB} = 2.0 V, 100 kHz ≤ f ≤ 1.0 MHz
SWITCHING CHARACTERISTICS					
t _{on}	Turn-On Time	-	45	ns	V _{CC} = 30 V, I _C = 150 mA, I _{B1} = 15 mA
t _{off}	Turn-Off Time	-	300	ns	V _{CC} = 30 V, I _C = 150 mA, I _{B1} = I _{B2} = 15 mA

Note:

1. Derate linearly 6.6 mW/° C above 25° C
2. Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0 %

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology
 2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200
 www.ttelectronics.com | sensors@ttelectronics.com

Surface Mount PNP General Purpose Transistor


2N2907AUB

Obsolete (2N2907AUBTX, 2N2907AUBTXV)



Standard Packaging:

Waffle Pack



Note:

1. Derate linearly 6.6 mW/° C above 25° C
2. Pulse Width $\leq 300 \mu\text{s}$, Duty Cycle $\leq 2.0 \%$

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

© TT electronics plc

TT Electronics | OPTEK Technology
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

Rev E 04/2022 Page 4