


# HC-M-KV-Z-M20

Order No.: 1646146

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1646146>

## Commercial data

|                          |  |
|--------------------------|--|
| GTIN (EAN)               | <br>4 017918 941284 |
| sales group              | D092   |
| Pack                     | 10 pcs.  |
| Customs tariff           | 74153300   |
| Catalog page information | Page 524 (PC-2009)   |

## Product notes

WEEE/RoHS-compliant since:  
04/07/2006

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

### General data

|                          |                     |
|--------------------------|---------------------|
| Cable gland material     | Nickel-plated brass |
| Material, pressure screw | Nickel-plated brass |
| Cable seal material      | Perbunan            |
| Material, O-ring         | NBR                 |
| Wrench size, union nut   | 27 mm               |
| Wrench size, support     | 24 mm               |

|  |                       |
|--|-----------------------|
| Thread type connection side 1            | M20                   |
| Conductor sealing range                  | 7.50 mm ... 15.00 mm  |
| Clamping range of the strain relief clip | 11.00 mm ... 17.00 mm |
| Degree of protection                     | IP65                  |
| Color                                    | silver                |
| Ambient temperature (operation)          | -20 °C ... 80 °C      |

### Diagrams/Drawings

Dimensioned drawing

---

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact  
Technical modifications reserved;