

Breather


T302-1xxx-zz

Body	Polyamide PA6 V-0
Filter element	Nonwoven
O-ring	Nitrile rubber NBR
Castle nut	Polyamide PA6 V-0
Connecting thread	metric, as per EN 60423



Properties

	<ul style="list-style-type: none"> • Application in electro-technical enclosures • continuous ventilation and drainage of the inside of enclosures • pressure equalization between the inside of enclosures and the ambient atmosphere • reduces condensation in enclosures • Installation at the lowest point of the enclosure bottom • Condensation, which collects on the bottom of the enclosure, can drain off via the vertically mounted breather • easy-to-install
Temperature range	-40 °C +100 °C
Protection grade	max. IP65 only when installed in the enclosure




Features



RAL 9005

Connecting thread standard length


A	L	SW1	SW2	H	RQ*	 VPE	Part No.
---	---	-----	-----	---	-----	--	----------

M20x1,5	10	27	27	21,6	ca. 1030	10	T302-1020-02
---------	----	----	----	------	----------	----	--------------



RAL 7035

Connecting thread standard length

A	L	SW1	SW2	H	RQ*	 VPE	Part No.
M20x1,5	10	27	27	21,6	ca. 1030	10	T302-1020-00

* RQ = theoretical air flow through usable surface at $\Delta p = 0,001$ bar