

RECOMMENDED SPARE PARTS.

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.

DWG NO 566185-1

PART NUMBER	REV	FIRST USED
566185-1	C	1-471273-2

APPLICATOR PARTS LIST				TYPE LENGTHWISE AMPLIVAR™ RING STUD RETAINING							
No.	DESCRIPTION	REQ.	PART NO.	No.	DESCRIPTION	REQ.	PART NO.	CRIMPING DATA		TERMINALS	
1	WIRE CRIMPER	1	456422-2	42				TO APPLY TERMINAL		S05044	
2	INS CRIMPER			43				WIRE SIZE			
3	ANVIL	1	473405-9	44				CRIMP HEIGHT			
4	ANVIL, INDENTER			45				20	.054		
5	SHEAR BLADE	1	2-465233-5	46				18	.057		
6	REAR SHEAR PLATE	1	385013	47				16	.062		
7	SHEAR BLADE SPACER	2	373072	48							
8	FRONT SHEAR PLATE	1	470857-3	49							
9	REAR ANVIL SPACER PL	1	1-470856-9	50				CRIMP	SIZE	TYPE	FEED
10	FRONT ANVIL SPACER PL			51				WIRE	.110	F	1.015
11	TOOL SPACER	1	378968	52				INSUL.			
12	CRIMP SPACER			53	HOLD DOWN (BLADE MT)	1	811065-1	SLEEVED			
13	FRONT STRIP GUIDE	1	379034-1	54				MAGNET		WIRE RANGE	
14	REAR STRIP GUIDE	1	379034-2	55	-	-	-			20-16	
15	RAM	1	471167	56				EXPLODED VIEW			
16	TOOL HOLDER	1	376046	57				A-6000		A-6000-1	
17	ADJ. CRIMP MOUNT			58				REMARKS:			
18	ADJ. BLOCK			59				FOR HARDWARE SEE			
19	APPLICATOR MOUNT	1	570656	60				8-687500-4			
20	BASE PLATE			61							
21	BASE BLOCK			62	NIPPLE, HEX 1/8 TO 3/8	1	22304-5				
22	STRIP GUIDE PL			63	VALVE. FLOW CONTROL	1	23054-1				
23	ANVIL HOLDER	1	370526	64	2" AIR FEED ASSY.	1	690021				
24	AUX. ANVIL HOLDER	1	377515	65	TENSION ADJ PLATE	1	374999				
25	STRIPPER	1	810872-1	MISCELLANEOUS							
26	STRIPPER MOUNT	1	386231	66	LUBRICATOR ASSY	1	465184-2				
27	RETAINING PLATE	1	372251	67	-	-	-				
28	STRIPPER MOUNT BRACKET			68	-	-	-				
29	STRIPPER BUSHING			69	-	-	-				
30	STOCK DRAG	1	375381	70							
31	STOCK DRAG HANDLE	-	-	71	-	-	-				
32	STOCK DRAG STUD	2	370583	72	-	-	-				
33	STOCK DRAG SPRING	2	1-23847-1					ALIGN GAGE 679597-1			
34	STOCK DRAG ADJ. SCREW	2	372997					AIR FEED			
35	FEED FINGER HOLDER							SERIAL NO.	DATE SHIPPED		
36	FEED FINGER	1	375093					CUSTOMER NAME AND ADDRESS			
37	FEED FINGER SPRING										
38	FEED FINGER PIN										
39	BASE CASTING	1	570238								
40	GUARD	1	457664-2								
41											

INACTIVE
FOR REPLACEMENT
ONLY

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO AMP INCORPORATED AND ITS WORLDWIDE SUBSIDIARIES AND AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN AMP PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM AMP INCORPORATED, HARRISBURG, PENNSYLVANIA USA.

LOC	A	DIST	4
C	0150-7386-96, STAT 7 WAS 4	20NOV96	DS CE
P	LTR	REVISION RECORD	DATE DWN APVD

FINISH	-	DWN	20NOV96	MATERIAL	-	HEAT TREAT	-
DIMENSIONS:	in	CHK	20NOV96	AMP Incorporated		Harrisburg, PA 17105-3608	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	20NOV96	J. DODDS			
0 PLC ±		NAME					
1 PLC ±		END FEED STD APPLICATOR					
2 PLC ±		SCALE	SIZE	DRAWING NO	SHEET	OF	REV
3 PLC ±		-	A3	566185-1	1	1	C
4 PLC ±							
ANGLES±	-						
SURFACE TEXTURE							