



Directive 2002/95/EC  
„RoHS“  
Compliant

**NOTES:**

1. PLATING MATING SIDE:  
INNER CONDUCTOR: min. 8µm HARD GOLD over min. 50µm NICKEL  
OUTER CONDUCTOR: min. 8µm HARD GOLD over min. 50µm NICKEL
2. IMPEDANCE: 50 OHM

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND

rev.	description	date	name	tolerance	dim. in mm
a	Origin				
		date	name		
		drawn 22.12.2009	Henneboel		
		appd. 22.12.2009	Koch		
		norm			
		d-old			



scale:	5:1	
material:		
title:	COAXIAL CONTACT PLUG 50 OHM Solder termination 90° with 3pins for D.SUB COMBINATION	
dwg no:	Inventor 10	DIN-A3
	13K1A3039	sh: 1
part no:	131A25019X	