


## High Performance Schottky Rectifier, 200 A


**TO-244**


### FEATURES

- 175 °C  $T_J$  operation
- Center tap module
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability
- UL approved file E222165
- Designed and qualified for industrial level
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
COMPLIANT

| PRIMARY CHARACTERISTICS |                           |
|-------------------------|---------------------------|
| $I_{F(AV)}$             | 200 A                     |
| $V_R$                   | 100 V                     |
| Package                 | TO-244                    |
| Circuit configuration   | Two diodes common cathode |

### DESCRIPTION / APPLICATIONS

The VS-203CNQ.. center tap Schottky rectifier module series has been optimized for low reverse leakage at high temperature. The proprietary barrier technology allows for reliable operation up to 175 °C junction temperature. Typical applications are in high current switching power supplies, plating power supplies, UPS systems, converters, freewheeling diodes, welding, and reverse battery protection.

| MAJOR RATINGS AND CHARACTERISTICS |   |             |                  |
|-----------------------------------|---|-------------|------------------|
| SYMBOL                            | CHARACTERISTICS   | VALUES      | UNITS            |
| $I_{F(AV)}$                       | Rectangular waveform  | 200         | A                |
| $V_{RRM}$                         |   | 100         | V                |
| $I_{FSM}$                         | $t_p = 5 \mu s$ sine  | 12 800      | A                |
| $V_F$                             | 100 $A_{pk}$ , $T_J = 125 \text{ }^\circ\text{C}$ (per leg) | 0.70        | V                |
| $T_J$                             | Range   | -55 to +175 | $^\circ\text{C}$ |

| VOLTAGE RATINGS                      |           |                 |       |
|--------------------------------------|-----------|-----------------|-------|
| PARAMETER                            | SYMBOL    | VS-203CNQ100PbF | UNITS |
| Maximum DC reverse voltage           | $V_R$     | 100             | V     |
| Maximum working peak reverse voltage | $V_{RWM}$ |                 |       |

| ABSOLUTE MAXIMUM RATINGS  |             |   |   |        |
|---|-------------|---|---|--------|
| PARAMETER   | SYMBOL      | TEST CONDITIONS   | VALUES  | UNITS  |
| Maximum average forward current<br>See fig. 5                             | $I_{F(AV)}$ | 50 % duty cycle at $T_C = 142 \text{ }^\circ\text{C}$ , rectangular waveform  | per leg   | 100    |
|   |             |   | per device  | 200    |
| Maximum peak one cycle non-repetitive surge current per leg<br>See fig. 7 | $I_{FSM}$   | 5 $\mu s$ sine or 3 $\mu s$ rect. pulse   | Following any rated load condition and with rated $V_{RRM}$ applied | 12 800 |
|   |             | 10 ms sine or 6 ms rect. pulse  |   | 1700   |
| Non-repetitive avalanche energy per leg                                   | $E_{AS}$    | $T_J = 25 \text{ }^\circ\text{C}$ , $I_{AS} = 13 \text{ A}$ , $L = 0.2 \text{ mH}$                                  | 15  | mJ     |
| Repetitive avalanche current per leg                                      | $I_{AR}$    | Current decaying linearly to zero in 1 $\mu s$<br>Frequency limited by $T_J$ maximum $V_A = 1.5 \times V_R$ typical | 1   | A      |



| ELECTRICAL SPECIFICATIONS                             |                |  |                                   |        |            |
|---|----------------|--|-----------------------------------|--------|------------|
| PARAMETER   | SYMBOL         | TEST CONDITIONS  |                                   | VALUES | UNITS      |
| Maximum forward voltage drop per leg<br>See fig. 1    | $V_{FM}^{(1)}$ | 100 A  | $T_J = 25\text{ }^\circ\text{C}$  | 0.86   | V          |
|   |                | 200 A  |                                   | 1.03   |            |
|   |                | 100 A  | $T_J = 125\text{ }^\circ\text{C}$ | 0.70   |            |
|   |                | 200 A  |                                   | 0.84   |            |
| Maximum reverse leakage current per leg<br>See fig. 2 | $I_{RM}^{(1)}$ | $T_J = 25\text{ }^\circ\text{C}$   | $V_R = \text{Rated } V_R$         | 3      | mA         |
|   |                | $T_J = 125\text{ }^\circ\text{C}$  |                                   | 40     |            |
| Threshold voltage                                     | $V_{F(TO)}$    | $T_J = T_J \text{ maximum}$  |                                   | 0.50   | V          |
| Forward slope resistance                              | $r_t$          | $T_J = T_J \text{ maximum}$  |                                   | 1.08   | m $\Omega$ |
| Maximum junction capacitance per leg                  | $C_T$          | $V_R = 5 V_{DC}$ (test signal range 100 kHz to 1 MHz) $25\text{ }^\circ\text{C}$ |                                   | 2650   | pF         |
| Typical series inductance per leg                     | $L_S$          | From top of terminal hole to mounting plane                                      |                                   | 7.0    | nH         |
| Maximum voltage rate of change                        | dV/dt          | Rated $V_R$  |                                   | 10 000 | V/ $\mu$ s |

**Note**

(1) Pulse width < 300  $\mu$ s, duty cycle < 2 %

| THERMAL - MECHANICAL SPECIFICATIONS            |                |            |      |          |                     |
|--|----------------|------------|------|----------|---------------------|
| PARAMETER                                      | SYMBOL         | MIN.       | TYP. | MAX.     | UNITS               |
| Maximum junction and storage temperature range | $T_J, T_{Stg}$ | -55        | -    | 175      | $^\circ\text{C}$    |
| Thermal resistance, junction to case           | $R_{thJC}$     | per leg    | -    | 0.38     | $^\circ\text{C/W}$  |
|  |                | per module | -    | 0.19     |                     |
| Thermal resistance, case to heatsink           | $R_{thCS}$     | -          | 0.10 | -        |                     |
| Weight   |                |            | 68   |          | g                   |
|  |                |            | 2.4  |          | oz.                 |
| Mounting torque                                |                | 35.4 (4)   | -    | 53.1 (6) | lbf · in<br>(N · m) |
| Mounting torque center hole                    |                | 30 (3.4)   | -    | 40 (4.6) |                     |
| Terminal torque                                |                | 30 (3.4)   | -    | 44.2 (5) |                     |
| Vertical pull                                  |                | -          | -    | 80       | lbf · in            |
| 2" lever pull                                  |                | -          | -    | 35       |                     |




Fig. 1 - Maximum Forward Voltage Drop Characteristics (Per Leg)




Fig. 2 - Typical Values of Reverse Current vs. Reverse Voltage (Per Leg)




Fig. 3 - Typical Junction Capacitance vs. Reverse Voltage (Per Leg)




Fig. 4 - Maximum Thermal Impedance  $Z_{thJC}$  Characteristics (Per Leg)




Fig. 5 - Maximum Allowable Case Temperature vs. Average Forward Current (Per Leg)




Fig. 6 - Forward Power Loss Characteristics (Per Leg)




Fig. 7 - Maximum Non-Repetitive Surge Current (Per Leg)




Fig. 8 - Unclamped Inductive Test Circuit

**Note**

- (1) Formula used:  $T_C = T_J - (P_d + P_{d_{REV}}) \times R_{thJC}$ ;  
 $P_d$  = forward power loss =  $I_{F(AV)} \times V_{FM}$  at  $(I_{F(AV)}/D)$  (see fig. 6);  
 $P_{d_{REV}}$  = inverse power loss =  $V_{R1} \times I_R (1 - D)$ ;  $I_R$  at  $V_{R1} = 80\%$  rated  $V_R$

**ORDERING INFORMATION TABLE**

|             |            |           |          |          |          |          |            |            |
|-------------|------------|-----------|----------|----------|----------|----------|------------|------------|
| Device code | <b>VS-</b> | <b>20</b> | <b>3</b> | <b>C</b> | <b>N</b> | <b>Q</b> | <b>100</b> | <b>PbF</b> |
|             | ①          | ②         | ③        | ④        | ⑤        | ⑥        | ⑦          | ⑧          |
|             | 1          | 2         | 3        | 4        | 5        | 6        | 7          | 8          |
|             |            |           |          |          |          |          |            |            |
|             |            |           |          |          |          |          |            |            |
|             |            |           |          |          |          |          |            |            |
|             |            |           |          |          |          |          |            |            |
|             |            |           |          |          |          |          |            |            |
|             |            |           |          |          |          |          |            |            |


**LINKS TO RELATED DOCUMENTS**

|            |  |
|------------|--|
| Dimensions | <a href="http://www.vishay.com/doc?95021">www.vishay.com/doc?95021</a> |
|------------|--|



## TO-244

**DIMENSIONS** in millimeters (inches)





## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.