1	2	3	4	5	
			20 TECHNICAL CHARACTER MATERIAL INSULATOR: PA 66 FLAMMABILITY RATING: COLOR: GREEN & ORAN COLOR: GREEN & ORAN CONTACT MATERIAL: CC CONTACT TATERIAL: CC CONTACT PLATING: TIN CONTACT TYPE: STAMPI FLANGES SCREW: STEE 2.30 ENVIRONMENTAL OPERATING TEMPERATI COMPLIANCE: LEAD FRE ELECTRICAL CURRENT RATING: WORKING VOLTAGE: WITHSTANDING VOLTAGE: WITHSTANDING VOLTAGE: STANDARD STANDARD SOLID WIRE: 22-	RISTICS UL94-V0 GE DPPER ALLOY ED :L M2.5 JRE: -40 UP TO 115°C EE AND ROHS CULus 5A 300VAC :E: 1.6KV 20 mOhm max 4 20 AWG / 0.326-0.518 MM ²	A B
RoHS Compliant G	PROJECTION:	GENERAL TOLERANCE			
F E D		.X = ⁺ /_ 0.2 .XX = ⁺ /_ 0.15			\vdash
C B A 08-JUN-15 PDF	APPROVAL: FBr	UNIT: MM SCALE: SHEET: 1/2	DESCRIPTION: SERIE 3593 - 3.81 MM IDC PLU WITH FLANGES WERI PART NO: 691 359 340 0xx	G HORIZONTAL ENTRY SIZE	יין
REV DATE FILE	BY	DRAW: AK	1		

1	2	3	4	5	-
					_

А

В

С

Cautions and Warnings:

This electronic component is designed and developed with the intention for use

in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

R	toHS Compliant							
G				PROJECTION:	GENERAL TOLERANCE			1
F					.X = ⁺ /_ 0.2			
E					.XX = ⁺ /_ 0.15			
D						WÜRTH ELEKTRONĬK		
С				APPROVAL: JC	UNIT: MM	DESCRIPTION: DISCLAIMER	SIZE	Ъ
В					SCALE:			Р
A	10-SEP-14	PDF	QL		SHEET: 2/2	WERI PART NO: DISCLAIMER	A4	
REV	DATE	FILE	BY		DRAW: QL			