

# RoHS

**NOTES:**

Insulator Material: PBT, UL 94V-0

Contact Plating: Flash Gold

Contact Material: Brass

Current Rating : 1A AC,DC





Contact Resistance: 20MΩ Max.

Dielectric Withstanding: AC 500V

Insulator Resistance: 1000MΩ Min.

Operating Temp.: -40°C~+105°C

REV.	DESCRIPTION	DATE
A	RELEASE	2012.11.12



NUMBER OF POSITIONS	DIMENSIONS	
	A	B
06	2.54	18.31
08	3.81	19.58
10	5.08	20.85
12	6.35	22.12
14	7.62	23.39
16	8.89	24.66
18	10.16	25.93
20	11.42	27.20
24	13.97	29.74
26	15.24	31.01
30	17.78	33.55
34	20.32	36.09
40	24.13	39.90
50	30.48	46.25
60	36.83	52.60
64	39.37	55.14

**CnC Tech,LLC**

Part No.

3210-XX-001-11-00

UNLESS TOLERANCE		DRAW BY		SCALE	SHEET	UNIT	DRAW NO:	REV: A
GENERAL	ANGLE	DESIGN BY	CHECK BY					
X. ± 0.30	X°. ± 3.0°			1:1	1/1	MM		
.X ± 0.20	.X° ± 2.0°							
.XX ± 0.15	.XX° ± 1.0°							
.XXX ± 0.08	.XXX ± 0.5°							

**P.C.B LAYOUT**

A

B

C

D

A

B

C

D

1 2 3 4 5 6