

**SN54HCT640, SN54HCT643, SN54HCT645
SN74HCT640, SN74HCT643, SN74HCT645
OCTAL BUS TRANSCEIVERS WITH 3-STATE OUTPUTS**

D2804, MARCH 1984—REVISED SEPTEMBER 1987

- Inputs are TTL-Voltage Compatible
- Choice of True or Inverting Logic
- High-Current 3-State Outputs Can Drive Up to 15 LSTTL Loads
- Package Options Include Plastic "Small Outline" Packages, Ceramic Chip Carriers, and Standard Plastic and Ceramic 300-mil DIPs
- Dependable Texas Instruments Quality and Reliability

| DEVICE | LOGIC |
|---------|--------------------|
| 'HCT640 | Inverting |
| 'HCT643 | True and Inverting |
| 'HCT645 | True |


description

These octal bus transceivers are designed for asynchronous two-way communication between data buses. The devices transmit data from the A bus to the B bus or from the B bus to the A bus depending upon the level at the direction control (DIR) input. The enable input (\bar{G}) can be used to disable the device so the buses are effectively isolated.


The SN54HCT640, SN54HCT643, and SN54HCT645 are characterized for operation over the full military temperature range of -55°C to 125°C . The SN74HCT640, SN74HCT643 and SN74HCT645 are characterized for operation from -40°C to 85°C .

**SN54HCT'... J PACKAGE
SN74HCT'... DW OR N PACKAGE**

(TOP VIEW)



**SN54HCT'... FK PACKAGE
(TOP VIEW)**



2

HCMOS Devices**FUNCTION TABLE**

| CONTROL INPUTS | OPERATION | | |
|----------------|-----------------|-----------------|-----------------|
| | 'HCT640 | 'HCT643 | 'HCT645 |
| L L | B data to A bus | B data to A bus | B data to A bus |
| L H | A data to B bus | A data to B bus | A data to B bus |
| H X | Isolation | Isolation | Isolation |

PRODUCTION DATA documents contain information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 1984, Texas Instruments Incorporated






POST OFFICE BOX 655012 • DALLAS, TEXAS 75265

2-553

**SN54HCT640, SN54HCT643, SN54HCT645
SN74HCT640, SN74HCT643, SN74HCT645
OCTAL BUS TRANSCEIVERS WITH 3-STATE OUTPUTS**

logic symbols†






2

HCMOS Devices

†These symbols are in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

logic diagrams (positive logic)



**SN54HCT640, SN54HCT643, SN54HCT645
SN74HCT640, SN74HCT643, SN74HCT645
OCTAL BUS TRANSCEIVERS WITH 3-STATE OUTPUTS**

T-52-31

absolute maximum ratings over operating free-air temperature range†

| | |
|---|----------------|
| Supply voltage, V _{CC} | -0.5 V to 7 V |
| Input clamp current, I _{IK} (V _I < 0 or V _I > V _{CC}) | ±20 mA |
| Output clamp current, I _{OK} (V _O < 0 or V _O > V _{CC}) | ±20 mA |
| Continuous output current, I _O (V _O = 0' to V _{CC}) | ±35 mA |
| Continuous current through V _{CC} or GND pins | ±70 mA |
| Lead temperature 1.6 mm (1/16 in) from case for 60 s: FK or J package | 300°C |
| Lead temperature 1.6 mm (1/16 in) from case for 10 s: DW or N package | 260°C |
| Storage temperature range | -65°C to 150°C |

† Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

2

HCMOS Devices

recommended operating conditions

| | | SN54HCT640 | | | SN74HCT640 | | | UNIT |
|--|----------------------------------|------------|-----------------|------------|------------|-----------------|-----|------|
| | | SN54HCT643 | SN74HCT643 | SN54HCT645 | SN74HCT645 | MIN | NOM | |
| V _{CC} Supply voltage | | 4.5 | 5 | 5.5 | 4.5 | 5 | 5.5 | V |
| V _{IH} High-level input voltage | V _{CC} = 4.5 V to 5.5 V | 2 | | | 2 | | | V |
| V _{IL} Low-level input voltage | V _{CC} = 4.5 V to 5.5 V | 0 | 0.8 | | 0 | 0.8 | | V |
| V _I Input voltage | | 0 | V _{CC} | | 0 | V _{CC} | | V |
| V _O Output voltage | | 0 | V _{CC} | | 0 | V _{CC} | | V |
| t _{tr} Input transition (rise and fall) times | | 0 | 500 | | 0 | 500 | | ns |
| T _A Operating free-air temperature | | -55 | 125 | -40 | 85 | | | °C |

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted).

| PARAMETER | TEST CONDITIONS | V _{CC} | T _A = 25°C | | | SN54HCT640 | | SN74HCT640 | | UNIT |
|--------------------|--|---------------------------------------|-----------------------|-------|-------|------------|-----|------------|-------|------|
| | | | MIN | TYP | MAX | MIN | MAX | MIN | MAX | |
| V _{OH} | V _I = V _{IH} or V _{IL} , I _{OH} = -20 μA | 4.5 V | 4.4 | 4.499 | | 4.4 | | 4.4 | | V |
| | V _I = V _{IH} or V _{IL} , I _{OH} = -6 mA | 4.5 V | 3.98 | 4.30 | | 3.7 | | 3.84 | | |
| V _{OL} | V _I = V _{IH} or V _{IL} , I _{OL} = 20 μA | 4.5 V | | 0.001 | 0.1 | | 0.1 | | 0.1 | V |
| | V _I = V _{IH} or V _{IL} , I _{OL} = 6 mA | 4.5 V | | 0.17 | 0.26 | | 0.4 | | 0.33 | |
| I _I | DIR or \bar{G} | V _I = V _{CC} or 0 | 5.5 V | | ±0.1 | ±100 | | ±1000 | ±1000 | nA |
| I _{OZ} | A or B | V _O = V _{CC} or 0 | 5.5 V | | ±0.01 | ±0.5 | | ±10 | ±5 | μA |
| I _{CC} | V _I = V _{CC} or 0, I _O = 0 | 5.5 V | | | 8 | | 160 | | 80 | μA |
| ΔI _{CC} ‡ | One Input at 0.5 V or 2.4 V Other Inputs at 0 V or V _{CC} | 5.5 V | | 1.4 | 2.4 | | 3 | | 2.9 | mA |
| C _I | DIR or \bar{G} | | 4.5 to 5.5 V | | 3 | 10 | | 10 | | pF |

‡This is the increase in supply current for each input that is at one of the specified TTL voltage levels rather than 0 V or V_{CC}.

T-52-31

SN54HCT640, SN54HCT643**SN74HCT640, SN74HCT643****OCTAL BUS TRANSCEIVERS WITH 3-STATE OUTPUTS**

switching characteristics over recommended operating free-air temperature range (unless otherwise noted), $C_L = 50 \text{ pF}$ (see Note 1)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | VCC | TA = 25°C | | | SN54HCT640 | SN74HCT640 | UNIT |
|------------------|-----------------|----------------|----------------|-----------|----------|-----|------------|------------|------|
| | | | | MIN | TYP | MAX | SN54HCT643 | SN74HCT643 | |
| t _{pd} | A or B | B or A | 4.5 V 5.5 V | 14 12 | 21 18 | | 32 27 | 25 23 | ns |
| t _{en} | — | A or B | 4.5 V 5.5 V | 27 24 | 35 32 | | 53 47 | 44 39 | ns |
| t _{dis} | — | A or B | 4.5 V 5.5 V | 20 18 | 30 26 | | 45 41 | 38 34 | ns |
| t _t | | A or B | 4.5 V 5.5 V | 9 8 | 12 11 | | 18 16 | 15 14 | ns |

| | | | |
|-----------------|---|--------------------|-----------|
| C _{pd} | Power dissipation capacitance per transceiver | No load, TA = 25°C | 40 pF typ |
|-----------------|---|--------------------|-----------|

switching characteristics over recommended operating free-air temperature range (unless otherwise noted), $C_L = 150 \text{ pF}$ (see Note 1)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | VCC | TA = 25°C | | | SN54HCT640 | SN74HCT640 | UNIT |
|-----------------|-----------------|----------------|----------------|-----------|----------|-----|------------|------------|------|
| | | | | MIN | TYP | MAX | SN54HCT643 | SN74HCT643 | |
| t _{pd} | A or B | B or A | 4.5 V 5.5 V | 17 15 | 27 24 | | 41 37 | 34 30 | ns |
| t _{en} | — | A or B | 4.5 V 5.5 V | 31 28 | 46 41 | | 68 61 | 56 51 | ns |
| t _t | | A or B | 4.5 V 5.5 V | 17 14 | 42 38 | | 63 57 | 53 48 | ns |

NOTE 1: Load circuits and voltage waveforms are shown in Section 1.

2

HCMOS Devices

2-556



POST OFFICE BOX 655012 • DALLAS, TEXAS 75265

SN54HCT645, SN74HCT645
OCTAL BUS TRANSCEIVERS WITH 3-STATE OUTPUTS

T-52-31

switching characteristics over recommended operating free-air temperature range (unless otherwise noted), $C_L = 50 \text{ pF}$ (see Note 1)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | V _{CC} | T _A = 25°C | | | SN54HCT645 | | SN74HCT645 | | UNIT |
|-----------|-----------------|----------------|-----------------|-----------------------|-----|-----|------------|-----|------------|-----|------|
| | | | | MIN | TYP | MAX | MIN | MAX | MIN | MAX | |
| t_{pd} | A or B | B or A | 4.5 V | 16 | 22 | 33 | | | 28 | | ns |
| | | | 5.5 V | 14 | 20 | 30 | | | 25 | | |
| t_{en} | \overline{G} | A or B | 4.5 V | 25 | 46 | 69 | | | 58 | | ns |
| | | | 5.5 V | 22 | 41 | 62 | | | 52 | | |
| t_{dis} | \overline{G} | A or B | 4.5 V | 26 | 40 | 60 | | | 50 | | ns |
| | | | 5.5 V | 23 | 36 | 54 | | | 45 | | |
| t_t | | A or B | 4.5 V | 9 | 12 | 18 | | | 15 | | ns |
| | | | 5.5 V | 8 | 11 | 16 | | | 14 | | |

| | | | |
|-----------------|---|--------------------------------|-----------|
| C _{pd} | Power dissipation capacitance per transceiver | No load, T _A = 25°C | 40 pF typ |
|-----------------|---|--------------------------------|-----------|

switching characteristics over recommended operating free-air temperature range (unless otherwise noted), $C_L = 150 \text{ pF}$ (see Note 1)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | V _{CC} | T _A = 25°C | | | SN54HCT645 | | SN74HCT645 | | UNIT |
|-----------|-----------------|----------------|-----------------|-----------------------|-----|-----|------------|-----|------------|-----|------|
| | | | | MIN | TYP | MAX | MIN | MAX | MIN | MAX | |
| t_{pd} | A or B | B or A | 4.5 V | 20 | 30 | 45 | | | 38 | | ns |
| | | | 5.5 V | 18 | 27 | 41 | | | 34 | | |
| t_{en} | \overline{G} | A or B | 4.5 V | 36 | 59 | 89 | | | 74 | | ns |
| | | | 5.5 V | 30 | 53 | 80 | | | 67 | | |
| t_t | | A or B | 4.5 V | 17 | 42 | 63 | | | 53 | | ns |
| | | | 5.5 V | 14 | 38 | 57 | | | 48 | | |

NOTE 1: Load circuits and voltage waveforms are shown in Section 1.

2

HCMOS Devices