

## Fiber optic cables - VS-P1212-P1218-C1001/ 2,0 - 1608906

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Assembled PROFINET-fiber optic cable, round cable, HCS fiber 200/230  $\mu\text{m}$ , SCRJ/IP67 push-pull metal housing on SCRJ/IP20, for installation inside buildings, length: 2 m



### Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	222.22 GRM
Custom tariff number	85447000
Country of origin	Germany

### Technical data

#### Mechanical characteristics

Number of positions	2
Connection profile	SCRJ in acc. with IEC 61754-24
Locking type	Push Pull
Fiber	200/230 $\mu\text{m}$
Number of fibers	2.00
Insertion/withdrawal cycles	$\geq 500$
Cable diameter	7.50 mm
Type of cable	Round cable
Length of cable	2 m

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 70 °C (cable, fixed installation)
	-10 °C ... 60 °C (cable, flexible installation)
	Plug / socket
Degree of protection	IP67/IP20

#### Material data

## Fiber optic cables - VS-P1212-P1218-C1001/ 2,0 - 1608906

### Technical data

#### Material data

Housing material	Zinc die-cast/PBT
Material, O-ring	NBR
Cable seal material	TPE
Outer sheath, material	LSFH
External sheath, color	green-yellow RAL 6018
Ferrule holder color	Red

#### Optical characteristics

Attenuation	≤ 1.2 dB (With 850 nm)
-------------	------------------------

### Classifications

#### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27061803
eCl@ss 6.0	27061090
eCl@ss 7.0	27061090

#### ETIM

ETIM 3.0	EC000034
ETIM 4.0	EC001476
ETIM 5.0	EC000034


#### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501


### Drawings

# Fiber optic cables - VS-P1212-P1218-C1001/ 2,0 - 1608906

Schematic diagram




Schematic diagram



Pin assignment plug SCRJ


Dimensioned drawing



SCRJ Push-Pull connector, IP67

Pin assignment plug SCRJ

Dimensioned drawing



SCRJ connector IP20